

---

# Tamr - Python Client Documentation

*Release 0.12*

Tamr

Jul 02, 2020



# CONTENTS

|  |           |
|--|-----------|
| <b>1 Example</b>                               | <b>3</b>  |
| <b>2 User Guide</b>                            | <b>5</b>  |
| 2.1 FAQ . . . . .                              | 5         |
| 2.2 Installation . . . . .                     | 6         |
| 2.3 Quickstart . . . . .                       | 7         |
| 2.4 Secure Credentials . . . . .               | 8         |
| 2.5 Workflows . . . . .                        | 10        |
| 2.6 Creating and Modifying Resources . . . . . | 11        |
| 2.7 Logging . . . . .                          | 13        |
| 2.8 Geospatial Data . . . . .                  | 14        |
| 2.9 Pandas Workflow . . . . .                  | 16        |
| 2.10 Advanced Usage . . . . .                  | 20        |
| <b>3 Reference</b>                             | <b>23</b> |
| 3.1 Reference . . . . .                        | 23        |
| <b>4 Contributor Guide</b>                     | <b>73</b> |
| 4.1 Contributor guide . . . . .                | 73        |
| <b>5 BETA</b>                                  | <b>81</b> |
| 5.1 BETA . . . . .                             | 81        |
| <b>Python Module Index</b>                     | <b>93</b> |
| <b>Index</b>                                   | <b>95</b> |



[View on Github](#)



---

**CHAPTER  
ONE**

---

**EXAMPLE**

```
from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth
import os

# grab credentials from environment variables
username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']
auth = UsernamePasswordAuth(username, password)

host = 'localhost' # replace with your Tamr host
tamr = Client(auth, host=host)

# programmatically interact with Tamr!
# e.g. refresh your project's Unified Dataset
project = tamr.projects.by_resource_id('3')
ud = project.unified_dataset()
op = ud.refresh()
assert op.succeeded()
```



## USER GUIDE

### 2.1 FAQ

#### 2.1.1 What version of the Python Client should I use?

The Python Client just cares about features, and will try everything it knows to implement those features correctly, independent of the API version.

If you are starting a new project or your existing project does not yet use the Python Client, we encourage you to use the **latest stable version** of the Python Client.

Otherwise, check the [Change Log](#) to see:

- what new features and bug fixes are available in newer versions
- which breaking changes (if any) will require changes in your code to get those new features and bug fixes

Note: You do not need to reason about the Tamr API version nor the the Tamr app/server version.

#### 2.1.2 How do I call custom endpoints, e.g. endpoints outside the Tamr API?

To call a custom endpoint *within* the Tamr API, use the `client.request()` method, and provide an endpoint described by a path relative to `base_path`.

For example, if `base_path` is `/api/versioned/v1/` (the default), and you want to get `/api/versioned/v1/projects/1`, you only need to provide `projects/1` (the relative ID provided by the project) as the endpoint, and the Client will resolve that into `/api/versioned/v1/projects/1`.

There are various APIs outside the `/api/versioned/v1/` prefix that are often useful or necessary to call - e.g. `/api/service/health`, or other un-versioned/unsupported APIs. To call a custom endpoint *outside* the Tamr API, use the `client.request()` method, and provide an endpoint described by an *absolute* path (a path starting with `/`). For example, to get `/api/service/health` (no matter what `base_path` is), call `client.request()` with `/api/service/health` as the endpoint. The Client will ignore `base_path` and send the request directly against the absolute path provided.

For additional detail, see [Raw HTTP requests and Unversioned API Access](<user-guide/advanced-usage:Raw HTTP requests and Unversioned API Access>)

## 2.2 Installation

`tamr-unify-client` is compatible with Python 3.6 or newer.

### 2.2.1 Stable releases

Installation is as simple as:

```
pip install tamr-unify-client
```

Or:

```
poetry add tamr-unify-client
```

---

**Note:** If you don't use `poetry`, we recommend you use a virtual environment for your project and install the Python Client into that virtual environment.

You can create a virtual environment with Python 3 via:

```
python3 -m venv my-venv
```

For more, see [The Hitchhiker's Guide to Python](#).

---

### 2.2.2 Latest (unstable)

---

**Note:** This project uses the new `pyproject.toml` file, not a `setup.py` file, so make sure you have the latest version of pip installed: `pip install -U pip`.

---

To install the bleeding edge:

```
git clone https://github.com/Datatamer/tamr-client
cd tamr-client
pip install .
```

### 2.2.3 Offline installs

First, download `tamr-unify-client` and its dependencies on a machine with online access to PyPI:

```
pip download tamr-unify-client -d tamr-unify-client-requirements
zip -r tamr-unify-client-requirements.zip tamr-unify-client-requirements
```

Then, ship the `.zip` file to the target machine where you want `tamr-unify-client` installed. You can do this via email, cloud drives, scp or any other mechanism.

Finally, install `tamr-unify-client` from the saved dependencies:

```
unzip tamr-unify-client-requirements.zip
pip install --no-index --find-links=tamr-unify-client-requirements tamr-unify-client
```

If you are not using a virtual environment, you may need to specify the `--user` flag if you get permissions errors:

```
pip install --user --no-index --find-links=tamr-unify-client-requirements tamr-unify-
    ↵client
```

## 2.3 Quickstart

### 2.3.1 Client configuration

Start by importing the Python Client and authentication provider:

```
from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth
```

Next, create an authentication provider and use that to create an authenticated client:

```
import os

username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']

auth = UsernamePasswordAuth(username, password)
tamr = Client(auth)
```

**Warning:** For security, it's best to read your credentials in from environment variables or secure files instead of hardcoding them directly into your code.

For more, see [User Guide > Secure Credentials](#).

By default, the client tries to find the Tamr instance on `localhost`. To point to a different host, set the `host` argument when instantiating the `Client`.

For example, to connect to `10.20.0.1`:

```
tamr = Client(auth, host='10.20.0.1')
```

### 2.3.2 Top-level collections

The Python Client exposes 2 top-level collections: Projects and Datasets.

You can access these collections through the client and loop over their members with simple `for-loops`.

E.g.:

```
for project in tamr.projects:
    print(project.name)

for dataset in tamr.datasets:
    print(dataset.name)
```

### 2.3.3 Fetch a specific resource

If you know the identifier for a specific resource, you can ask for it directly via the `by_resource_id` methods exposed by collections.

E.g. To fetch the project with ID '1':

```
project = tamr.projects.by_resource_id('1')
```

Similarly, if you know the name of a specific resource, you can ask for it directly via the `by_name` methods exposed by collections.

E.g. To fetch the project with name 'Number 1':

```
project = tamr.projects.by_name('Number 1')
```

---

**Note:** If working with projects across Tamr instances for migrations or promotions, use external IDs (via `by_external_id`) instead of name (via `by_name`).

---

### 2.3.4 Resource relationships

Related resources (like a project and its unified dataset) can be accessed through specific methods.

E.g. To access the Unified Dataset for a particular project:

```
ud = project.unified_dataset()
```

### 2.3.5 Kick-off Tamr Operations

Some methods on Model objects can kick-off long-running Tamr operations.

Here, kick-off a “Unified Dataset refresh” operation:

```
operation = project.unified_dataset().refresh()  
assert op.succeeded()
```

By default, the API Clients expose a synchronous interface for Tamr operations.

## 2.4 Secure Credentials

This section discusses ways to pass credentials securely to `UsernamePasswordAuth`. Specifically, you **should not** hardcode your password(s) in your source code. Instead, you should use environment variables or secure files to store your credentials and simple Python code to read your credentials.

## 2.4.1 Environment variables

You can use `os.environ` to read in your credentials from environment variables:

```
# my_script.py
import os

from tamr_unify_client.auth import UsernamePasswordAuth

username = os.environ['TAMR_USERNAME'] # replace with your username environment
# variable name
password = os.environ['TAMR_PASSWORD'] # replace with your password environment
# variable name

auth = UsernamePasswordAuth(username, password)
```

You can pass in the environment variables from the terminal by including them before your command:

```
TAMR_USERNAME="my Tamr username" TAMR_PASSWORD="my Tamr password" python my_script.py
```

You can also create an `.sh` file to store your environment variables and simply source that file before running your script.

## 2.4.2 Config files

You can also store your credentials in a secure credentials file:

```
# credentials.yaml
---
username: "my tamr username"
password: "my tamr password"
```

Then `pip install pyyaml` read the credentials in your Python code:

```
# my_script.py
from tamr_unify_client.auth import UsernamePasswordAuth
import yaml

with open("path/to/credentials.yaml") as f: # replace with your credentials.yaml path
    creds = yaml.safe_load(f)

auth = UsernamePasswordAuth(creds['username'], creds['password'])
```

As in this example, we recommend you use YAML as your format since YAML has support for comments and is more human-readable than JSON.

---

**Important:** You **should not** check these credentials files into your version control system (e.g. git). Do not share this file with anyone who should not have access to the password stored in it.

---

## 2.5 Workflows

### 2.5.1 Continuous Categorization

```
from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth
import os

username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']
auth = UsernamePasswordAuth(username, password)

host = 'localhost' # replace with your host
tamr = Client(auth)

project_id = "1" # replace with your project ID
project = tamr.projects.by_resource_id(project_id)
project = project.as_categorization()

unified_dataset = project.unified_dataset()
op = unified_dataset.refresh()
assert op.succeeded()

model = project.model()
op = model.train()
assert op.succeeded()

op = model.predict()
assert op.succeeded()
```

### 2.5.2 Continuous Mastering

```
from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth
import os

username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']
auth = UsernamePasswordAuth(username, password)

host = 'localhost' # replace with your host
tamr = Client(auth)

project_id = "1" # replace with your project ID
project = tamr.projects.by_resource_id(project_id)
project = project.as_mastering()

unified_dataset = project.unified_dataset()
op = unified_dataset.refresh()
assert op.succeeded()

op = project.pairs().refresh()
assert op.succeeded()
```

(continues on next page)

(continued from previous page)

```
model = project.pair_matching_model()
op = model.train()
assert op.succeeded()

op = model.predict()
assert op.succeeded()

op = project.record_clusters().refresh()
assert op.succeeded()

op = project.published_clusters().refresh()
assert op.succeeded()
```

## 2.6 Creating and Modifying Resources

### 2.6.1 Creating resources

Resources, such as projects, dataset, and attribute configurations, can be created through their respective collections. Each `create` function takes in a dictionary that conforms to the [Tamr Public Docs](#) for creating that resource type:

```
spec = {
    "name": "project",
    "description": "Mastering Project",
    "type": "DEDUP",
    "unifiedDatasetName": "project_unified_dataset"
}
project = tamr.projects.create(spec)
```

### 2.6.2 Using specs

These dictionaries can also be created using `Spec` classes.

Each `Resource` has a corresponding `ResourceSpec` which can be used to build an instance of that resource by specifying the value for each property.

The spec can then be converted to a dictionary that can be passed to `create`.

For instance, to create a project:

```
spec = (
    ProjectSpec.new()
    .with_name("Project")
    .with_type("DEDUP")
    .with_description("Mastering Project")
    .with_unified_dataset_name("Project_unified_dataset")
    .with_external_id("tamrProject1")
)
project = tamr.projects.create(spec.to_dict())
```

Calling `with_*` on a spec creates a new spec with the same properties besides the modified one. The original spec is unaltered, so it could be used multiple times:

```
base_spec = (
    ProjectSpec.new()
    .with_type("DEDUP")
    .with_description("Mastering Project")
)

specs = []
for name in project_names:
    spec = (
        base_spec.with_name(name)
        .with_unified_dataset_name(name + "_unified_dataset")
    )
    specs.append(spec)

projects = [tamr.projects.create(spec.to_dict()) for spec in specs]
```

### 2.6.3 Creating a dataset

Datasets can be created as described above, but the dataset's schema and records must then be handled separately.

To combine all of these steps into one, `DatasetCollection` has a convenience function `create_from_dataframe` that takes a Pandas `DataFrame`. This makes it easy to create a Tamr dataset from a CSV:

```
import pandas as pd

df = pd.read_csv("my_data.csv", dtype=str)      # string is the recommended data type
dataset = tamr.datasets.create_from_dataframe(df, primary_key_name="primary key name",
    ↴ dataset_name="My Data")
```

This will create a dataset called "My Data" with the specified primary key, an attribute for each column of the `DataFrame`, and the `DataFrame`'s rows as records.

### 2.6.4 Modifying a resource

Certain resources can also be modified using specs.

After getting a spec corresponding to a resource and modifying some properties, the updated resource can be committed to Tamr with the `put` function:

```
updated_dataset = (
    dataset.spec()
    .with_description("Modified description")
    .put()
)
```

Each spec class has many properties that can be changed, but refer to the [Public Docs](#) for which properties will actually be updated in Tamr. If an immutable property is changed in the update request, the new value will simply be ignored.

## 2.7 Logging

**IMPORTANT** Make sure to configure logging BEFORE importing from 3rd party libraries. Logging will use the first configuration it finds, and if a library configures logging before you, your configuration will be ignored.

To configure logging, simply follow the [official Python logging HOWTO](#).

For example:

```
# script.py
import logging

logging.basicConfig(filename="script.log", level=logging.INFO)

# configure logging before other imports

from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth

auth = UsernamePasswordAuth("my username", "my password")
tamr = Client(auth, host="myhost")

for p in tamr.projects:
    print(p)

for d in tamr.datasets:
    print(d)

# should cause an HTTP error
tamr.get("/invalid/api/path").successful()
```

This will log all API requests made and print the response bodies for any requests with HTTP error codes.

If you want to **only** configure logging for the Tamr Client:

```
import logging
logger = logging.getLogger('tamr_unify_client')
logger.setLevel(logging.INFO)
logger.addHandler(logging.FileHandler('tamr-client.log'))

# configure logging before other imports

from tamr_unify_client import Client
from tamr_unify_client import UsernamePasswordAuth

# rest of script goes here
```

## 2.8 Geospatial Data

### 2.8.1 What geospatial data is supported?

In general, the Python Geo Interface is supported; see <https://gist.github.com/sgillies/2217756>.

There are three layers of information, modeled after GeoJSON (see <https://tools.ietf.org/html/rfc7946>):

- The outermost layer is a FeatureCollection
  - type (string; required)
  - id (object; required)
  - geometry (Geometry, see below; optional)
  - bbox (“bounding box”, 4 doubles; optional)
  - properties (map[string, object]; optional)
- Within a FeatureCollection are Features, each of which represents one “thing”, like a building or a river. Each feature has:
  - type (one of “Point”, “MultiPoint”, “LineString”, “MultiLineString”, “Polygon”, “MultiPolygon”; required)
  - coordinates (doubles; exactly how these are structured depends on the type of the geometry)

Although the Python Geo Interface is non-prescriptive when it comes to the data types of the id and properties, Tamr has a more restricted set of supported types. See <https://docs.tamr.com/reference#attribute-types>.

The Dataset class supports the `__geo_interface__` property. This will produce one FeatureCollection for the entire dataset.

There is a companion iterator `itergeofeatures()` that returns a generator that allows you to stream the records in the dataset as Geospatial features.

To produce a GeoJSON representation of a dataset:

```
dataset = client.datasets.by_name("my_dataset")
with open("my_dataset.json", "w") as f:
    json.dump(dataset.__geo_interface__, f)
```

By default, `itergeofeatures()` will use the first dataset attribute with geometry type to fill in the feature geometry. You can override this by specifying the `geometry` attribute to use in the `geo_attr` parameter to `itergeofeatures`.

Dataset can also be updated from a feature collection that supports the Python Geo Interface:

```
import geopandas
geodataframe = geopandas.GeoDataFrame(...)
dataset = client.dataset.by_name("my_dataset")
dataset.from_geo_features(geodataframe)
```

Note that there are currently some limitations to GeoPandas’ implementation of the Geo Interface. See below for more details.

By default the features’ geometries will be placed into the first dataset attribute with geometry type. You can override this by specifying the `geometry` attribute to use in the `geo_attr` parameter to `from_geo_features`.

## 2.8.2 Rules for converting from Tamr records to Geospatial Features

The record's primary key will be used as the feature's `id`. If the primary key is a single attribute, then the value of that attribute will be the value of `id`. If the primary key is composed of multiple attributes, then the value of the `id` will be an array with the values of the key attributes in order.

Tamr allows any number of geometry attributes per record; the Python Geo Interface is limited to one. When converting Tamr records to Python Geo Features, the first geometry attribute in the schema will be used as the geometry; all other geometry attributes will appear as properties with no type conversion. In the future, additional control over the handling of multiple geometries may be provided; the current set of capabilities is intended primarily to support the use case of working with FeatureCollections within Tamr, and FeatureCollection has only one geometry per feature.

An attribute is considered to have geometry type if it has type RECORD and contains an attribute named `point`, `multiPoint`, `lineString`, `multiLineString`, `polygon`, or `multiPolygon`.

If an attribute named `bbox` is available, it will be used as `bbox`. No conversion is done on the value of `bbox`. In the future, additional control over the handling of `bbox` attributes may be provided.

All other attributes will be placed in `properties`, with no type conversion. This includes all geometry attributes other than the first.

## 2.8.3 Rules for converting from Geospatial Features to Tamr records

The Feature's `id` will be converted into the primary key for the record. If the record uses a simple key, no value translation will be done. If the record uses a composite key, then the value of the Feature's `id` must be an array of values, one per attribute in the key.

If the Feature contains keys in `properties` that conflict with the record keys, `bbox`, or `geometry`, those keys are ignored (omitted).

If the Feature contains a `bbox`, it is copied to the record's `bbox`.

All other keys in the Feature's `properties` are propagated to the same-name attribute on the record, with no type conversion.

## 2.8.4 Streaming data access

The Dataset method `itergeofeatures()` returns a generator that allows you to stream the records in the dataset as Geospatial features:

```
my_dataset = client.datasets.by_name("my_dataset")
for feature in my_dataset.itergeofeatures():
    do_something(feature)
```

Note that many packages that consume the Python Geo Interface will be able to consume this iterator directly. For example::

```
from geopandas import GeoDataFrame
df = GeoDataFrame.from_features(my_dataset.itergeofeatures())
```

This allows construction of a GeoDataFrame directly from the stream of records, without materializing the intermediate dataset.

## 2.8.5 Note on GeoPandas data access

There is a current limitation in [GeoPandas](#) that causes the feature's ID field to be ignored in certain scenarios. The Tamr primary key is stored in this field. The result is that when loading data and updating records through the `dataset.from_geo_features()` method, records will not be overwritten as anticipated.

This issue can be circumvented by loading features into GeoPandas by re-inserting the id field into the data.

```
my_dataset = client.datasets.by_name("my_dataset")
for feature in my_dataset.itergeofeatures():
    primary_key = feature['id']
    df = gpd.GeoDataFrame.from_features([feature])
    do_something(df)
    geo.index = [primary_key]
    my_dataset.from_geo_features(df)
```

Alternatively, it is possible to load the full dataset as follows:

```
my_dataset = client.datasets.by_name("my_dataset")
def geopandas_dataset(dataset):
    for feature in dataset.itergeofeatures():
        feature['properties']['primary_key'] = feature['id']
        yield feature
df = gpd.GeoDataFrame.from_features(geopandas_dataset(my_dataset))
df.set_index('primary_key')
do_something(df)
my_dataset.from_geo_features(df)
```

## 2.9 Pandas Workflow

### 2.9.1 Connecting To Tamr

Connecting to a Tamr instance:

```
import os
import pandas as pd
from tamr_unify_client import Client
from tamr_unify_client.auth import UsernamePasswordAuth

username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']

auth = UsernamePasswordAuth(username, password)
tamr = Client(auth)
```

## 2.9.2 Load dataset as Dataframe

### Loading: In Memory

Loading a dataset as a pandas dataframe is possible via the `from_records()` method that pandas provides. An example is shown below:

```
my_dataset = tamr.datasets.by_name("my_tamr_dataset")
df = pd.DataFrame.from_records(my_dataset.records())
```

This will construct a pandas dataframe based on the records that are streamed in, and stored in the pandas dataframe. Once all records have been loaded, you will be able to interact with the dataframe normally.

Note that as values are typically represented inside `arrays` within Tamr, the values will be encapsulated `lists` inside the dataframe. You can use traditional methods in pandas to deal with this; for example by calling `.explode()`, or extracting specific elements.

### Loading: Streaming

When working with large datasets it is sometimes better not to work in memory, but to iterate through a dataset, rather than load the entire dataset at once. Since `dataset.records()` is a generator, this can easily be done as follows:

```
output = []
for record in dataset.records():
    single_record_df = pd.DataFrame.from_records(record)
    output.append(do_something(single_record_df))
```

### Custom Generators

In order to customise the data loaded into the pandas dataframe, it is possible to customise the generator object `dataset.records()` by wrapping it in a different generator.

For example, it is possible to automatically flatten all lists with a length of one, and apply this to the `dataset.records()` generator as follows:

```
def unlist(lst):
    """
    If object is a list of length one, return first element.
    Otherwise, return original object.
    """
    if isinstance(lst, list) and len(lst) == 1:
        return lst[0]
    else:
        return lst

def dataset_to_pandas(dataset):
    """
    Incorporates basic unlisting for easy transfer between Tamr and Pandas.
    """
    for record in dataset.records():
        for key in record:
            record[key] = unlist(record[key])
        yield record
```

(continues on next page)

(continued from previous page)

```
df = pd.DataFrame.from_records(dataset_to_pandas(my_dataset))
```

Similarly, it is possible to filter to extracting only certain attributes, by specifying this in the generator:

```
def filter_dataset_to_pandas(dataset, colnames):
    """
    Filter the dataset to only the primary key and the columns specified as a list in
    colnames.
    """
    assert isinstance(colnames, list)
    colnames = dataset.key_attribute_names + colnames if dataset.key_attribute_
    names[0] not in colnames else colnames
    for record in dataset.records():
        yield {k: unlist(v) for k, v in record.items() if k in colnames}

df = pd.DataFrame.from_records(filter_dataset_to_pandas(my_dataset, ['City', 'new_attr
']))
```

Note that upserting these records back to the original Tamr Dataset would overwite the existing records and attributes, and cause loss of the data stored in the removed attributes.

## 2.9.3 Upload Dataframe as Dataset

### Create New Dataset

To create a new dataset and upload data, the convenience function `dataset.create_from_dataframe()` can be used. Note that Tamr will throw an error if columns aren't generally formatted as strings. (The exception being geospatial columns. For that, see the geospatial examples.)

In order to achieve this, the following code will transform the column types to string.

```
df = df.astype(str)
```

Creating the dataset is as easy as calling:

```
tamr.datasets.create_from_dataframe(df, 'primaryKey', 'my_new_dataset')
```

### Changing Values

#### Making Changes: In Memory

When making changes to a dataset that was loaded as a dataframe, changes can be pushed back to Tamr using the `dataset.upsert_from_dataframe()` method as follows:

```
df = pd.DataFrame.from_records(my_dataset.records())
df['column'] = 'new_value'
my_dataset.upsert_from_dataframe(df, primary_key_name='primary_key')
```

## Making Changes: Streaming

For larger datasets it might be better to stream the data and apply changes while iterating through the dataset. This way the full dataset does not need to be loaded into memory.

```
for record in dataset.records():
    single_record_df = pd.DataFrame.from_records(record)
    single_record_df['column_to_change'] = 'new_value'
    dataset.upsert_from_dataframe(single_record_df, primary_key_name='primary_key')
```

## Adding Attributes

When making changes to dataframes, new dataframe columns are not automatically created as attributes when upserting records to Tamr. In order for these changes to be recorded, these attributes first need to be created.

One way of creating these for source datasets automatically would be as follows:

```
def add_missing_attributes(dataset, df):
    """
    Detects any attributes in the dataframe that aren't in the dataset and attempts
    to add them (as strings).
    """
    existing_attributes = [att.name for att in dataset.attributes]
    new_attributes = [att for att in df.columns.to_list() if att not in existing_
    attributes]

    if not new_attributes:
        return

    for new_attribute in new_attributes:
        attr_spec = {"name": new_attribute,
                     "type": {"baseType": "ARRAY", "innerType": {"baseType": "STRING"}}
        },
        }
        dataset.attributes.create(attr_spec)

add_missing_attributes(my_dataset, df)
```

## 2.9.4 Troubleshooting

When running into errors upon loading `dataset.records()` into a pandas dataframe, it is good to consider the following steps. To extract a single record, the following code can be used to provide a minimal reproducible example:

```
record = next(dataset.records())
print(record)
```

## Parsing

Tamr allows for more variety in attribute names and contents than pandas does. In most cases pandas can load data correctly, but it is possible to modify the parsing using a custom generator as shown above. An example below changes an attribute name, and extracts only the first element:

```
def custom_parser(dataset):
    for record in dataset.records():
        record['pandas_column_name'] = record.pop('dataset_attribute_name')
        record['first_element_of_column'] = record['multi_value_column'][0]
        yield record

df = pd.DataFrame.from_records(custom_parser(dataset))
```

## 2.10 Advanced Usage

### 2.10.1 Asynchronous Operations

You can opt-in to an asynchronous interface via the `asynchronous` keyword argument for methods that kick-off Tamr operations.

E.g.:

```
op = project.unified_dataset().refresh(asynchronous=True)
# do asynchronous stuff here while operation is running
op = op.wait() # hangs until operation finishes
assert op.succeeded()
```

### 2.10.2 Raw HTTP requests and Unversioned API Access

We encourage you to use the high-level, object-oriented interface offered by the Python Client. If you aren't sure whether you need to send low-level HTTP requests, you probably don't.

But sometimes it's useful to directly send HTTP requests to Tamr; for example, Tamr has many APIs that are not covered by the higher-level interface (most of which are neither versioned nor supported). You can still call these endpoints using the Python Client, but you'll need to work with raw `Response` objects.

## Custom endpoint

The client exposes a `request` method with the same interface as `requests.request`:

```
# import Python Client library and configure your client

tamr = Client(auth)
# do stuff with the `tamr` client

# now I NEED to send a request to a specific endpoint
response = tamr.request('GET', 'relative/path/to/resource')
```

This will send a request relative to the `base_path` registered with the client. If you provide an absolute path to the resource, the `base_path` will be ignored when composing the request:

```
# import Python Client library and configure your client

tamr = Client(auth)

# request a resource outside the configured base_path
response = tamr.request('GET', '/absolute/path/to/resource')
```

You can also use the `get`, `post`, `put`, `delete` convenience methods:

```
# e.g. `get` convenience method
response = tamr.get('relative/path/to/resource')
```

## Custom Host / Port / Base API path

If you need to repeatedly send requests to another port or base API path (i.e. not `/api/versioned/v1/`), you can simply instantiate a different client.

Then just call `request` as described above:

```
# import Python Client library and configure your client

tamr = api.Client(auth)
# do stuff with the `tamr` client

# now I NEED to send requests to a different host/port/base API path etc..
# NOTE: in this example, we reuse `auth` from the first client, but we could
# have made a new Authentication provider if this client needs it.
custom_client = api.Client(
    auth,
    host="10.10.0.1",
    port=9090,
    base_path="/api/some_service/",
)
response = custom_client.get('relative/path/to/resource')
```

## One-off authenticated request

All of the Python Client Authentication providers adhere to the `requests.auth.BaseAuth` interface.

This means that you can pass in an Authentication provider directly to the `requests` library:

```
from tamr_unify_client.auth import UsernamePasswordAuth
import os
import requests

username = os.environ['TAMR_USERNAME']
password = os.environ['TAMR_PASSWORD']
auth = UsernamePasswordAuth(username, password)

response = requests.request('GET', 'some/specific/endpoint', auth=auth)
```

## REFERENCE

### 3.1 Reference

#### 3.1.1 Attributes

##### Attribute

```
class tamr_unify_client.attribute.resource.Attribute(client, data, alias=None)
```

A Tamr Attribute.

See <https://docs.tamr.com/reference#attribute-types>

```
property relative_id
```

str

Type type

```
property name
```

str

Type type

```
property description
```

str

Type type

```
property type
```

AttributeType

Type type

```
property is_nullable
```

bool

Type type

```
spec()
```

Returns a spec representation of this attribute.

**Returns** The attribute spec.

**Return type** AttributeSpec

```
delete()
```

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property resource\_id**  
str

**Type** `type`

## Attribute Spec

**class** `tamr_unify_client.attribute.resource.AttributeSpec(client, data, api_path)`  
A representation of the server view of an attribute

**static of(resource)**  
Creates an attribute spec from an attribute.

**Parameters** `resource (Attribute)` – The existing attribute.

**Returns** The corresponding attribute spec.

**Return type** `AttributeSpec`

**static new()**  
Creates a blank spec that could be used to construct a new attribute.

**Returns** The empty spec.

**Return type** `AttributeSpec`

**from\_data(data)**  
Creates a spec with the same client and API path as this one, but new data.

**Parameters** `data (dict)` – The data for the new spec.

**Returns** The new spec.

**Return type** `AttributeSpec`

**to\_dict()**  
Returns a version of this spec that conforms to the API representation.

**Returns** The spec's dict.

**Return type** `dict`

**with\_name(new\_name)**  
Creates a new spec with the same properties, updating name.

**Parameters** `new_name (str)` – The new name.

**Returns** The new spec.

**Return type** `AttributeSpec`

**with\_description(new\_description)**  
Creates a new spec with the same properties, updating description.

**Parameters** `new_description (str)` – The new description.

**Returns** The new spec.

**Return type** `AttributeSpec`

**with\_type(new\_type)**  
Creates a new spec with the same properties, updating type.

**Parameters** `new_type (AttributeTypeSpec)` – The spec of the new type.

**Returns** The new spec.

**Return type** `AttributeSpec`

**with\_is\_nullable** (`new_is_nullable`)

Creates a new spec with the same properties, updating is nullable.

**Parameters** `new_is_nullable` (`bool`) – The new is nullable.

**Returns** The new spec.

**Return type** `AttributeSpec`

**put()**

Commits the changes and updates the attribute in Tamr.

**Returns** The updated attribute.

**Return type** `Attribute`

## Attribute Collection

```
class tamr_unify_client.attribute.collection.AttributeCollection(client,  
                                                               api_path)
```

Collection of `Attribute`s.

**Parameters**

- `client` (`Client`) – Client for API call delegation.
- `api_path` (`str`) – API path used to access this collection. E.g. "datasets/1/attributes".

**by\_resource\_id** (`resource_id`)

Retrieve an attribute by resource ID.

**Parameters** `resource_id` (`str`) – The resource ID. E.g. "AttributeName"

**Returns** The specified attribute.

**Return type** `Attribute`

**by\_relative\_id** (`relative_id`)

Retrieve an attribute by relative ID.

**Parameters** `relative_id` (`str`) – The resource ID. E.g. "datasets/1/attributes/AttributeName"

**Returns** The specified attribute.

**Return type** `Attribute`

**by\_external\_id** (`external_id`)

Retrieve an attribute by external ID.

Since attributes do not have external IDs, this method is not supported and will raise a `NotImplementedError`.

**Parameters** `external_id` (`str`) – The external ID.

**Returns** The specified attribute, if found.

**Return type** `Attribute`

**Raises**

- **KeyError** – If no attribute with the specified external\_id is found
- **LookupError** – If multiple attributes with the specified external\_id are found

**stream()**

Stream attributes in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of attributes.

**Return type** Python generator yielding *Attribute*

**Usage:**

```
>>> for attribute in collection.stream(): # explicit
>>>     do_stuff(attribute)
>>> for attribute in collection: # implicit
>>>     do_stuff(attribute)
```

**by\_name** (*attribute\_name*)

Lookup a specific attribute in this collection by exact-match on name.

**Parameters** **attribute\_name** (*str*) – Name of the desired attribute.

**Returns** Attribute with matching name in this collection.

**Return type** *Attribute*

**create** (*creation\_spec*)

Create an Attribute in this collection

**Parameters** **creation\_spec** (*dict[str, str]*) – Attribute creation specification  
should be formatted as specified in the [Public Docs for adding an Attribute](#).

**Returns** The created Attribute

**Return type** *Attribute*

**delete\_by\_resource\_id** (*resource\_id*)

Deletes a resource from this collection by resource ID.

**Parameters** **resource\_id** (*str*) – The resource ID of the resource that will be deleted.

**Returns** HTTP response from the server.

**Return type** *requests.Response*

## Attribute Type

**class** tamr\_unify\_client.attribute.type.**AttributeType** (*data*)

The type of an [Attribute](#) or [SubAttribute](#).

See <https://docs.tamr.com/reference#attribute-types>

**Parameters** **data** (*dict*) – JSON data representing this type

**property** **base\_type**

*str*

**Type** *type*

**property** **inner\_type**

*AttributeType*

**Type** *type*

---

```
property attributes
list[SubAttribute]

Type type

spec()
    Returns a spec representation of this attribute type.

    Returns The attribute type spec.

    Return type AttributeTypeSpec
```

## Attribute Type Spec

```
class tamr_unify_client.attribute.type.AttributeTypeSpec (data)

static of (resource)
    Creates an attribute type spec from an attribute type.

    Parameters resource (AttributeType) – The existing attribute type.

    Returns The corresponding attribute type spec.

    Return type AttributeTypeSpec

static new()
    Creates a blank spec that could be used to construct a new attribute type.

    Returns The empty spec.

    Return type AttributeTypeSpec

to_dict()
    Returns a version of this spec that conforms to the API representation.

    Returns The spec's dict.

    Return type dict

with_base_type (new_base_type)
    Creates a new spec with the same properties, updating the base type.

    Parameters new_base_type (str) – The new base type.

    Returns The new spec.

    Return type AttributeTypeSpec

with_inner_type (new_inner_type)
    Creates a new spec with the same properties, updating the inner type.

    Parameters new_inner_type (AttributeTypeSpec) – The spec of the new inner type.

    Returns The new spec.

    Return type AttributeTypeSpec

with_attributes (new_attributes)
    Creates a new spec with the same properties, updating attributes.

    Parameters new_attributes (list[AttributeSpec]) – The specs of the new attributes.

    Returns The new spec.

    Return type AttributeTypeSpec
```

## SubAttribute

```
class tamr_unify_client.attribute.subattribute.SubAttribute(name, type,
                                                               is_nullable, _json,
                                                               description=None)
```

An attribute which is itself a property of another attribute.

See <https://docs.tamr.com/reference#attribute-types>

### Parameters

- **name** (`str`) – Name of sub-attribute
- **description** (`Optional[str]`) – Description of sub-attribute
- **type** (`AttributeType`) – See <https://docs.tamr.com/reference#attribute-types>
- **is\_nullable** (`bool`) – If this sub-attribute can be null

```
static from_json(data)
```

Create a SubAttribute from JSON data.

**Parameters** `data` (`Dict[str, Any]`) – JSON data received from Tamr server.

**Return type** `SubAttribute`

## 3.1.2 Auth

```
class tamr_unify_client.auth.UsernamePasswordAuth(username, password)
```

Provides username/password authentication for Tamr. Specifically, sets the *Authorization* HTTP header with Tamr's custom *BasicCreds* format.

### Parameters

- **username** (`str`) –
- **password** (`str`) –

**Usage:**

```
>>> from tamr_unify_client.auth import UsernamePasswordAuth
>>> auth = UsernamePasswordAuth('my username', 'my password')
>>> import tamr_unify_client as api
>>> unify = api.Client(auth)
```

## 3.1.3 Categorization

### Categorization Project

```
class tamr_unify_client.categorization.project.CategorizationProject(client,
                                                                     data,
                                                                     alias=None)
```

A Categorization project in Tamr.

```
model()
```

Machine learning model for this Categorization project. Learns from verified labels and predicts categorization labels for unlabeled records.

**Returns** The machine learning model for categorization.

**Return type** `MachineLearningModel`

**create\_taxonomy** (`creation_spec`)  
Creates a `Taxonomy` for this project.  
A taxonomy cannot already be associated with this project.

**Parameters** `creation_spec` (`dict`) – The creation specification for the taxonomy, which can include name.

**Returns** The new Taxonomy

**Return type** `Taxonomy`

**taxonomy()**  
Retrieves the `Taxonomy` associated with this project. If a taxonomy is not already associated with this project, call `create_taxonomy()` first.

**Returns** The project's Taxonomy

**Return type** `Taxonomy`

**add\_input\_dataset** (`dataset`)  
Associate a dataset with a project in Tamr.  
By default, datasets are not associated with any projects. They need to be added as input to a project before they can be used as part of that project

**Parameters** `dataset` (`Dataset`) – The dataset to associate with the project.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**as\_categorization()**  
Convert this project to a `CategorizationProject`

**Returns** This project.

**Return type** `CategorizationProject`

**Raises** `TypeError` – If the `type` of this project is not "CATEGORIZATION"

**as\_mastering()**  
Convert this project to a `MasteringProject`

**Returns** This project.

**Return type** `MasteringProject`

**Raises** `TypeError` – If the `type` of this project is not "DEDUP"

**attribute\_configurations()**  
Project's attribute's configurations.

**Returns** The configurations of the attributes of a project.

**Return type** `AttributeConfigurationCollection`

**attribute\_mappings()**  
Project's attribute's mappings.

**Returns** The attribute mappings of a project.

**Return type** `AttributeMappingCollection`

**property\_attributes**  
Attributes of this project.

**Returns** Attributes of this project.

**Return type** *AttributeCollection*

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** *requests.Response*

**property description**  
str

**Type** *type*

**property external\_id**  
str

**Type** *type*

**input\_datasets()**  
Retrieve a collection of this project's input datasets.

**Returns** The project's input datasets.

**Return type** *DatasetCollection*

**property name**  
str

**Type** *type*

**property relative\_id**  
str

**Type** *type*

**remove\_input\_dataset(dataset)**  
Remove a dataset from a project.

**Parameters** **dataset** (*Dataset*) – The dataset to be removed from this project.

**Returns** HTTP response from the server

**Return type** *requests.Response*

**property resource\_id**  
str

**Type** *type*

**spec()**  
Returns this project's spec.

**Returns** The spec for the project.

**Return type** *ProjectSpec*

**property type**  
*//docs.tamr.com/reference#create-a-project.*

**Type** str

**Type** A Tamr project type, listed in https

**unified\_dataset()**  
Unified dataset for this project.

**Returns** Unified dataset for this project.

**Return type** *Dataset*

## Categories

### Category

```
class tamr_unify_client.categorization.category.resource.Category(client, data,
alias=None)
```

A category of a taxonomy

**property name**

str

**Type** *type*

**property description**

str

**Type** *type*

**property path**

list[str]

**Type** *type*

**parent()**

Gets the parent Category of this one, or None if it is a tier 1 category

**Returns** The parent Category or None

**Return type** *Category*

**spec()**

Returns this category's spec.

**Returns** The spec for the category.

**Return type** *CategorySpec*

**delete()**

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** *requests.Response*

**property relative\_id**

str

**Type** *type*

**property resource\_id**

str

**Type** *type*

## Category Spec

```
class tamr_unify_client.categorization.category.resource.CategorySpec(client,
                                                                     data,
                                                                     api_path)
```

A representation of the server view of a category.

**static of**(resource)

Creates a category spec from a category.

**Parameters** resource (*Category*) – The existing category.

**Returns** The corresponding category spec.

**Return type** *CategorySpec*

**static new**()

Creates a blank spec that could be used to construct a new category.

**Returns** The empty spec.

**Return type** *CategorySpec*

**from\_data**(data)

Creates a spec with the same client and API path as this one, but new data.

**Parameters** data (*dict*) – The data for the new spec.

**Returns** The new spec.

**Return type** *CategorySpec*

**to\_dict**()

Returns a version of this spec that conforms to the API representation.

**Returns** The spec's dict.

**Return type** *dict*

**with\_name**(new\_name)

Creates a new spec with the same properties, updating name.

**Parameters** new\_name (*str*) – The new name.

**Returns** The new spec.

**Return type** *CategorySpec*

**with\_description**(new\_description)

Creates a new spec with the same properties, updating description.

**Parameters** new\_description (*str*) – The new description.

**Returns** The new spec.

**Return type** *CategorySpec*

**with\_path**(new\_path)

Creates a new spec with the same properties, updating path.

**Parameters** new\_path (*list[str]*) – The new path.

**Returns** The new spec.

**Return type** *CategorySpec*

## Category Collection

```
class tamr_unify_client.categorization.category.collection.CategoryCollection(client,
                                                                           api_path)
```

Collection of *Category* s.

### Parameters

- **client** (*Client*) – Client for API call delegation.
- **api\_path** (*str*) – API path used to access this collection. E.g. "projects/1/taxonomy/categories".

#### **by\_resource\_id**(resource\_id)

Retrieve a category by resource ID.

**Parameters** **resource\_id** (*str*) – The resource ID. E.g. "1"

**Returns** The specified category.

**Return type** *Category*

#### **by\_relative\_id**(relative\_id)

Retrieve a category by relative ID.

**Parameters** **relative\_id** (*str*) – The relative ID. E.g. "projects/1/categories/1"

**Returns** The specified category.

**Return type** *Category*

#### **by\_external\_id**(external\_id)

Retrieve an attribute by external ID.

Since categories do not have external IDs, this method is not supported and will raise a `NotImplementedError`.

**Parameters** **external\_id** (*str*) – The external ID.

**Returns** The specified category, if found.

**Return type** *Category*

### Raises

- **KeyError** – If no category with the specified external\_id is found
- **LookupError** – If multiple categories with the specified external\_id are found

#### **stream**()

Stream categories in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of categories.

**Return type** Python generator yielding *Category*

### Usage:

```
>>> for category in collection.stream(): # explicit
>>>     do_stuff(category)
>>> for category in collection: # implicit
>>>     do_stuff(category)
```

**create** (*creation\_spec*)

Creates a new category.

**Parameters** `creation_spec` (`dict`) – Category creation specification, formatted as specified in the [Public Docs for Creating a Category](#).

**Returns** The newly created category.

**Return type** `Category`

**bulk\_create** (*creation\_specs*)

Creates new categories in bulk.

**Parameters** `creation_specs` (`iterable[dict]`) – A collection of creation specifications, as detailed for `create`.

**Returns** JSON response from the server

**Return type** `dict`

**delete\_by\_resource\_id** (*resource\_id*)

Deletes a resource from this collection by resource ID.

**Parameters** `resource_id` (`str`) – The resource ID of the resource that will be deleted.

**Returns** HTTP response from the server.

**Return type** `requests.Response`

## Taxonomy

**class** `tamr_unify_client.categorization.taxonomy.Taxonomy` (*client, data, alias=None*)

A project's taxonomy

**property** `name`

`str`

**Type** `type`

**categories** ()

Retrieves the categories of this taxonomy.

**Returns** A collection of the taxonomy categories.

**Return type** `CategoryCollection`

**delete** ()

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property** `relative_id`

`str`

**Type** `type`

**property** `resource_id`

`str`

**Type** `type`

### 3.1.4 Client

```
class tamr_unify_client.Client(auth, host='localhost', protocol='http', port=9100,
                                base_path='/api/versioned/v1/', session=None)
```

Python Client for Tamr API.

Each client is specific to a specific origin (protocol, host, port).

#### Parameters

- **auth** (`AuthBase`) – Tamr-compatible Authentication provider.  
**Recommended:** use one of the classes described in [Authentication](#)
- **host** (`str`) – Host address of remote Tamr instance (e.g. '10.0.10.0')
- **protocol** (`str`) – Either 'http' or 'https'
- **port** (`Optional[int]`) – Tamr instance main port
- **base\_path** (`str`) – Base API path. Requests made by this client will be relative to this path.
- **session** (`Optional[Session]`) – Session to use for API calls. If none is provided, will use a new `requests.Session`.

#### Example

```
>>> from tamr_unify_client import Client
>>> from tamr_unify_client.auth import UsernamePasswordAuth
>>> auth = UsernamePasswordAuth('my username', 'my password')
>>> tamr_local = Client(auth) # on http://localhost:9100
>>> tamr_remote = Client(auth, protocol='https', host='10.0.10.0') # on https://
-> 10.0.10.0:9100
>>> tamr_remote = Client(auth, protocol='https', host='10.0.10.0', port=None) #_
-> on https://10.0.10.0
```

#### property `origin`

HTTP origin i.e. <protocol>://<host>[:<port>].

For additional information, see [MDN web docs](#).

#### Return type `str`

#### `request` (`method, endpoint, **kwargs`)

Sends a request to Tamr.

The URL for the request will be <origin>/<base\_path>/<endpoint>. The request is authenticated via `Client.auth`.

#### Parameters

- **method** (`str`) – The HTTP method to use (e.g. 'GET' or 'POST')
- **endpoint** (`str`) – API endpoint to call (relative to the Base API path for this client).

#### Return type `Response`

Returns HTTP response from the Tamr server

#### `get` (`endpoint, **kwargs`)

Calls `request()` with the "GET" method.

```
post (endpoint, **kwargs)
    Calls request() with the "POST" method.

put (endpoint, **kwargs)
    Calls request() with the "PUT" method.

delete (endpoint, **kwargs)
    Calls request() with the "DELETE" method.

property projects
    Collection of all projects on this Tamr instance.

    Return type ProjectCollection

    Returns Collection of all projects.

property datasets
    Collection of all datasets on this Tamr instance.

    Return type DatasetCollection

    Returns Collection of all datasets.
```

### 3.1.5 Datasets

#### Dataset

```
class tamr_unify_client.dataset.resource.Dataset (client, data, alias=None)
    A Tamr dataset.

    property name
        str

        Type type

    property external_id
        str

        Type type

    property description
        str

        Type type

    property version
        str

        Type type

    property tags
        list[str]

        Type type

    property key_attribute_names
        list[str]

        Type type

    property attributes
        Attributes of this dataset.

        Returns Attributes of this dataset.
```

**Return type** `AttributeCollection`

**upsert\_from\_dataframe** (`df`, \*, `primary_key_name`, `ignore_nan=True`)

Upserts a record for each row of `df` with attributes for each column in `df`.

**Parameters**

- `df` (`pd.DataFrame`) – The data to upsert records from.
- `primary_key_name` (`str`) – The name of the primary key of the dataset. Must be a column of `df`.
- `ignore_nan` (`bool`) – Whether to convert `Nan` values to `null` before upserting records to Tamr. If `False` and `Nan` is in `df`, this function will fail. Optional, default is `True`.

**Return type** `dict`

**Returns** JSON response body from the server.

**Raises** `KeyError` – If `primary_key_name` is not a column in `df`.

**upsert\_records** (`records`, `primary_key_name`, \*\*`json_args`)

Creates or updates the specified records.

**Parameters**

- `records` (`iterable[dict]`) – The records to update, as dictionaries.
- `primary_key_name` (`str`) – The name of the primary key for these records, which must be a key in each record dictionary.
- `**json_args` – Arguments to pass to the JSON `dumps` function, as documented [here](#). Some of these, such as `indent`, may not work with Tamr.

**Returns** JSON response body from the server.

**Return type** `dict`

**delete\_records** (`records`, `primary_key_name`)

Deletes the specified records.

**Parameters**

- `records` (`iterable[dict]`) – The records to delete, as dictionaries.
- `primary_key_name` (`str`) – The name of the primary key for these records, which must be a key in each record dictionary.

**Returns** JSON response body from the server.

**Return type** `dict`

**delete\_records\_by\_id** (`record_ids`)

Deletes the specified records.

**Parameters** `record_ids` (`iterable`) – The IDs of the records to delete.

**Returns** JSON response body from the server.

**Return type** `dict`

**delete\_all\_records** ()

Removes all records from the dataset.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**refresh** (\*\*options)

Brings dataset up-to-date if needed, taking whatever actions are required.

**Parameters** **\*\*options** – Options passed to underlying *Operation* . See [apply\\_options\(\)](#).

**Returns** The refresh operation.

**Return type** *Operation*

**profile**()

Returns profile information for a dataset.

If profile information has not been generated, call `create_profile()` first. If the returned profile information is out-of-date, you can call `refresh()` on the returned object to bring it up-to-date.

**Returns** Dataset Profile information.

**Return type** *DatasetProfile*

**create\_profile**(\*\*options)

Create a profile for this dataset.

If a profile already exists, the existing profile will be brought up to date.

**Parameters** **\*\*options** – Options passed to underlying *Operation* . See [apply\\_options\(\)](#).

**Returns** The operation to create the profile.

**Return type** *Operation*

**records**()

Stream this dataset's records as Python dictionaries.

**Returns** Stream of records.

**Return type** Python generator yielding *dict*

**status**()

Retrieve this dataset's streamability status.

**Returns** Dataset streamability status.

**Return type** *DatasetStatus*

**usage**()

Retrieve this dataset's usage by recipes and downstream datasets.

**Returns** The dataset's usage.

**Return type** *DatasetUsage*

**from\_geo\_features**(features, geo\_attr=None)

Upsert this dataset from a geospatial FeatureCollection or iterable of Features.

*features* can be:

- An object that implements `__geo_interface__` as a FeatureCollection (see <https://gist.github.com/sgillies/2217756>)
- An iterable of features, where each element is a feature dictionary or an object that implements the `__geo_interface__` as a Feature
- A map where the “features” key contains an iterable of features

See: `geopandas.GeoDataFrame.from_features()`

If `geo_attr` is provided, then the named Tamr attribute will be used for the geometry. If `geo_attr` is not provided, then the first attribute on the dataset with geometry type will be used for the geometry.

#### Parameters

- `features` – geospatial features
- `geo_attr` (`str`) – (optional) name of the Tamr attribute to use for the feature's geometry

**Returns** JSON response body from server.

**Return type** `dict`

#### `upstream_datasets()`

The Dataset's upstream datasets.

API returns the URIs of the upstream datasets, resulting in a list of `DatasetURI`s, not actual Datasets.

**Returns** A list of the Dataset's upstream datasets.

**Return type** `list[DatasetURI]`

#### `spec()`

Returns this dataset's spec.

**Returns** The spec of this dataset.

**Return type** `DatasetSpec`

#### `delete(cascade=False)`

Deletes this dataset, optionally deleting all derived datasets as well.

**Parameters** `cascade` (`bool`) – Whether to delete all datasets derived from this one. Optional, default is `False`. Do not use this option unless you are certain you need it as it can have unintended consequences.

**Returns** HTTP response from the server

**Return type** `requests.Response`

#### `itergeofeatures(geo_attr=None)`

Returns an iterator that yields feature dictionaries that comply with `__geo_interface__`

See <https://gist.github.com/sgillies/2217756>

**Parameters** `geo_attr` (`str`) – (optional) name of the Tamr attribute to use for the feature's geometry

**Returns** stream of features

**Return type** Python generator yielding `dict[str, object]`

#### `property relative_id`

`str`

**Type** `type`

#### `property resource_id`

`str`

**Type** `type`

## Dataset Spec

```
class tamr_unify_client.dataset.resource.DatasetSpec(client, data, api_path)
```

A representation of the server view of a dataset.

```
static of(resource)
```

Creates a dataset spec from a dataset.

**Parameters** `resource` (`Dataset`) – The existing dataset.

**Returns** The corresponding dataset spec.

**Return type** `DatasetSpec`

```
static new()
```

Creates a blank spec that could be used to construct a new dataset.

**Returns** The empty spec.

**Return type** `DatasetSpec`

```
from_data(data)
```

Creates a spec with the same client and API path as this one, but new data.

**Parameters** `data` (`dict`) – The data for the new spec.

**Returns** The new spec.

**Return type** `DatasetSpec`

```
to_dict()
```

Returns a version of this spec that conforms to the API representation.

**Returns** The spec's dict.

**Return type** `dict`

```
with_name(new_name)
```

Creates a new spec with the same properties, updating name.

**Parameters** `new_name` (`str`) – The new name.

**Returns** A new spec.

**Return type** `DatasetSpec`

```
with_external_id(new_external_id)
```

Creates a new spec with the same properties, updating external ID.

**Parameters** `new_external_id` (`str`) – The new external ID.

**Returns** A new spec.

**Return type** `DatasetSpec`

```
with_description(new_description)
```

Creates a new spec with the same properties, updating description.

**Parameters** `new_description` (`str`) – The new description.

**Returns** A new spec.

**Return type** `DatasetSpec`

```
with_key_attribute_names(new_key_attribute_names)
```

Creates a new spec with the same properties, updating key attribute names.

**Parameters** `new_key_attribute_names` (`list[str]`) – The new key attribute names.

**Returns** A new spec.

**Return type** `DatasetSpec`

**with\_tags** (`new_tags`)  
Creates a new spec with the same properties, updating tags.

**Parameters** `new_tags` (`list[str]`) – The new tags.

**Returns** A new spec.

**Return type** `DatasetSpec`

**put()**  
Updates the dataset on the server.

**Returns** The modified dataset.

**Return type** `Dataset`

## Dataset Collection

```
class tamr_unify_client.dataset.collection.DatasetCollection(client,
                                                               api_path='datasets')
```

Collection of `Dataset`s.

### Parameters

- `client` (`Client`) – Client for API call delegation.
- `api_path` (`str`) – API path used to access this collection. E.g. "projects/1/inputDatasets". Default: "datasets".

**by\_resource\_id** (`resource_id`)

Retrieve a dataset by resource ID.

**Parameters** `resource_id` (`str`) – The resource ID. E.g. "1"

**Returns** The specified dataset.

**Return type** `Dataset`

**by\_relative\_id** (`relative_id`)

Retrieve a dataset by relative ID.

**Parameters** `relative_id` (`str`) – The resource ID. E.g. "datasets/1"

**Returns** The specified dataset.

**Return type** `Dataset`

**by\_external\_id** (`external_id`)

Retrieve a dataset by external ID.

**Parameters** `external_id` (`str`) – The external ID.

**Returns** The specified dataset, if found.

**Return type** `Dataset`

### Raises

- `KeyError` – If no dataset with the specified external\_id is found
- `LookupError` – If multiple datasets with the specified external\_id are found

**stream()**

Stream datasets in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of datasets.

**Return type** Python generator yielding *Dataset*

**Usage:**

```
>>> for dataset in collection.stream(): # explicit
>>>     do_stuff(dataset)
>>> for dataset in collection: # implicit
>>>     do_stuff(dataset)
```

**by\_name** (*dataset\_name*)

Lookup a specific dataset in this collection by exact-match on name.

**Parameters** **dataset\_name** (*str*) – Name of the desired dataset.

**Returns** Dataset with matching name in this collection.

**Return type** *Dataset*

**Raises** **KeyError** – If no dataset with specified name was found.

**delete\_by\_resource\_id** (*resource\_id*, *cascade=False*)

Deletes a dataset from this collection by resource\_id. Optionally deletes all derived datasets as well.

**Parameters**

- **resource\_id** (*str*) – The resource id of the dataset in this collection to delete.
- **cascade** (*bool*) – Whether to delete all datasets derived from the deleted one. Optional, default is *False*. Do not use this option unless you are certain you need it as it can have unintended consequences.

**Returns** HTTP response from the server.

**Return type** *requests.Response*

**create** (*creation\_spec*)

Create a Dataset in Tamr

**Parameters** **creation\_spec** (*dict[str, str]*) – Dataset creation specification should be formatted as specified in the [Public Docs for Creating a Dataset](#).

**Returns** The created Dataset

**Return type** *Dataset*

**create\_from\_dataframe** (*df*, *primary\_key\_name*, *dataset\_name*, *ignore\_nan=True*)

Creates a dataset in this collection with the given name, creates an attribute for each column in the *df* (with *primary\_key\_name* as the key attribute), and upserts a record for each row of *df*.

Each attribute has the default type *ARRAY[STRING]*, besides the key attribute, which will have type *STRING*.

This function attempts to ensure atomicity, but it is not guaranteed. If an error occurs while creating attributes or records, an attempt will be made to delete the dataset that was created. However, if this request errors, it will not try again.

**Parameters**

- **df** ([pandas.DataFrame](#)) – The data to create the dataset with.

- **primary\_key\_name** (`str`) – The name of the primary key of the dataset. Must be a column of `df`.
- **dataset\_name** (`str`) – What to name the dataset in Tamr. There cannot already be a dataset with this name.
- **ignore\_nan** (`bool`) – Whether to convert `NaN` values to `null` before upserting records to Tamr. If `False` and `NaN` is in `df`, this function will fail. Optional, default is `True`.

**Returns** The newly created dataset.

**Return type** `Dataset`

#### Raises

- **KeyError** – If `primary_key_name` is not a column in `df`.
- **CreationError** – If a step in creating the dataset fails.

```
class tamr_unify_client.dataset.collection.CreationError(error_message)
An error from create_from_dataframe()

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.
```

## Dataset Profile

```
class tamr_unify_client.dataset.profile.DatasetProfile(client, data, alias=None)
Profile info of a Tamr dataset.

property dataset_name
The name of the associated dataset.

Type str
Return type str

property relative_dataset_id
The relative dataset ID of the associated dataset.

Type str
Return type str

property is_up_to_date
Whether the associated dataset is up to date.

Type bool
Return type bool

property profiled_data_version
The profiled data version.

Type str
Return type str

property profiled_at
Info about when profile info was generated.

Type dict
Return type dict
```

**property simple\_metrics**

Simple metrics for profiled dataset.

**Type** `list`

**Return type** `list`

**property attribute\_profiles**

Simple metrics for profiled dataset.

**Type** `list`

**Return type** `list`

**refresh(\*\*options)**

Updates the dataset profile if needed.

The dataset profile is updated on the server; you will need to call `profile()` to retrieve the updated profile.

**Parameters** `**options` – Options passed to underlying `Operation`. See `apply_options()`.

**Returns** The refresh operation.

**Return type** `Operation`

**delete()**

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property relative\_id**

`str`

**Type** `type`

**property resource\_id**

`str`

**Type** `type`

## Dataset Status

**class tamr\_unify\_client.dataset.status.DatasetStatus(client, data, alias=None)**

Streamability status of a Tamr dataset.

**property dataset\_name**

The name of the associated dataset.

**Type** `str`

**Return type** `str`

**property relative\_dataset\_id**

The relative dataset ID of the associated dataset.

**Type** `str`

**Return type** `str`

**property is\_streamable**

Whether the associated dataset is available to be streamed.

**Type** `bool`

**Return type** `bool`

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property relative\_id**  
`str`

**Type** `type`

**property resource\_id**  
`str`

**Type** `type`

## Dataset URI

**class** `tamr_unify_client.dataset.uri.DatasetURI(client, uri)`  
Identifier of a dataset.

### Parameters

- **client** (`Client`) – Queried dataset’s client.
- **uri** (`str`) – Queried dataset’s dataset ID.

**property resource\_id**  
`str`

**Type** `type`

**property relative\_id**  
`str`

**Type** `type`

**property uri**  
`str`

**Type** `type`

**dataset()**

Fetch the dataset that this identifier points to.

**Returns** A Tamr dataset.

**Return type**

**class** `~tamr_unify_client.dataset.resource.Dataset`

## Dataset Usage

```
class tamr_unify_client.dataset.usage.DatasetUsage(client, data, alias=None)
    The usage of a dataset and its downstream dependencies.

    See https://docs.tamr.com/reference#retrieve-downstream-dataset-usage

    property relative_id
        str

        Type type

    property usage
        DatasetUse

        Type type

    property dependencies
        list[DatasetUse]

        Type type

    delete()
        Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

        Returns HTTP response from the server

        Return type requests.Response

    property resource_id
        str

        Type type
```

## Dataset Use

```
class tamr_unify_client.dataset.use.DatasetUse(client, data)
    The use of a dataset in project steps. This is not a BaseResource because it has no API path and cannot be directly retrieved or modified.

    See https://docs.tamr.com/reference#retrieve-downstream-dataset-usage

    Parameters
        • client (Client) – Delegate underlying API calls to this client.
        • data (dict) – The JSON body containing usage information.

    property dataset_id
        str

        Type type

    property dataset_name
        str

        Type type

    property input_to_project_steps
        list[ProjectStep]

        Type type

    property output_from_project_steps
        list[ProjectStep]
```

**Type** `type`

**dataset()**  
Retrieves the `Dataset` this use represents.

**Returns** The dataset being used.

**Return type** `Dataset`

### 3.1.6 Machine Learning Model

```
class tamr_unify_client.base_model.MachineLearningModel(client, data, alias=None)
```

A Tamr Machine Learning model.

**train(\*\*options)**  
Learn from verified labels.

**Parameters** `**options` – Options passed to underlying `Operation`. See `apply_options()`.

**Returns** The resultant operation.

**Return type** `Operation`

**predict(\*\*options)**  
Suggest labels for unverified records.

**Parameters** `**options` – Options passed to underlying `Operation`. See `apply_options()`.

**Returns** The resultant operation.

**Return type** `Operation`

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property relative\_id**  
`str`

**Type** `type`

**property resource\_id**  
`str`

**Type** `type`

### 3.1.7 Mastering

#### Binning Model

```
class tamr_unify_client.mastering.binning_model.BinningModel(client, data, alias=None)
```

A binning model object.

**records()**  
Stream this object's records as Python dictionaries.

**Returns** Stream of records.

**Return type** Python generator yielding `dict`

**update\_records** (`records`)

Send a batch of record creations/updates/deletions to this dataset.

**Parameters** `records` (`iterable[dict]`) – Each record should be formatted as specified in the [Public Docs for Dataset updates](#).

**Returns** JSON response body from server.

**Return type** `dict`

**delete** ()

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property relative\_id**

str

**Type** `type`

**property resource\_id**

str

**Type** `type`

## Estimated Pair Counts

```
class tamr_unify_client.mastering.estimated_pair_counts.EstimatedPairCounts (client,  
                                data,  
                                alias=None)
```

Estimated Pair Counts info for Mastering Project

**property is\_up\_to\_date**

Whether an estimate pairs job has been run since the last edit to the binning model.

**Return type** `bool`

**property total\_estimate**

The total number of estimated candidate pairs and generated pairs for the model across all clauses.

**Returns**

A dictionary containing candidate pairs and estimated pairs mapped to their corresponding estimated counts. For example:

```
{  
    "candidatePairCount": "54321",  
    "generatedPairCount": "12345"  
}
```

**Return type** `dict[str, str]`

**property clause\_estimates**

The estimated candidate pair count and generated pair count for each clause in the model.

**Returns**

A dictionary containing each clause name mapped to a dictionary containing the corresponding estimated candidate and generated pair counts. For example:

```
{  
    "Clause1": {  
        "candidatePairCount": "321",  
        "generatedPairCount": "123"  
    },  
    "Clause2": {  
        "candidatePairCount": "654",  
        "generatedPairCount": "456"  
    }  
}
```

**Return type** `dict[str, dict[str, str]]`

**refresh(\*\*options)**

Updates the estimated pair counts if needed.

The pair count estimates are updated on the server; you will need to call `estimate_pairs()` to retrieve the updated estimate.

**Parameters** `**options` – Options passed to underlying `Operation`. See `apply_options()`.

**Returns** The refresh operation.

**Return type** `Operation`

**delete()**

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property relative\_id**

str

**Type** `type`

**property resource\_id**

str

**Type** `type`

## Mastering Project

```
class tamr_unify_client.mastering.project.MasteringProject(client,          data,
                                                               alias=None)
```

A Mastering project in Tamr.

### pairs()

Record pairs generated by Tamr's binning model. Pairs are displayed on the "Pairs" page in the Tamr UI.

Call `refresh()` from this dataset to regenerate pairs according to the latest binning model.

**Returns** The record pairs represented as a dataset.

**Return type** `Dataset`

### pair\_matching\_model()

Machine learning model for pair-matching for this Mastering project. Learns from verified labels and predicts categorization labels for unlabeled pairs.

Calling `predict()` from this dataset will produce new (unpublished) clusters. These clusters are displayed on the "Clusters" page in the Tamr UI.

**Returns** The machine learning model for pair-matching.

**Return type** `MachineLearningModel`

### high\_impact\_pairs()

High-impact pairs as a dataset. Tamr labels pairs as "high-impact" if labeling these pairs would help it learn most quickly (i.e. "Active learning").

High-impact pairs are displayed with a lightning bolt icon on the "Pairs" page in the Tamr UI.

Call `refresh()` from this dataset to produce new high-impact pairs according to the latest pair-matching model.

**Returns** The high-impact pairs represented as a dataset.

**Return type** `Dataset`

### record\_clusters()

Record Clusters as a dataset. Tamr clusters labeled pairs using pairs model. These clusters populate the cluster review page and get transient cluster ids, rather than published cluster ids (i.e., "Permanent Ids")

Call `refresh()` from this dataset to generate clusters based on to the latest pair-matching model.

**Returns** The record clusters represented as a dataset.

**Return type** `Dataset`

### published\_clusters()

Published record clusters generated by Tamr's pair-matching model.

**Returns** The published clusters represented as a dataset.

**Return type** `Dataset`

### published\_clusters\_configuration()

Retrieves published clusters configuration for this project.

**Returns** The published clusters configuration

**Return type** `PublishedClustersConfiguration`

### published\_cluster\_ids()

Retrieves published cluster IDs for this project.

**Returns** The published cluster ID dataset.

**Return type** `Dataset`

**published\_cluster\_stats()**  
Retrieves published cluster stats for this project.

**Returns** The published cluster stats dataset.

**Return type** `Dataset`

**published\_cluster\_versions(cluster\_ids)**  
Retrieves version information for the specified published clusters. See <https://docs.tamr.com/reference#retrieve-published-clusters-given-cluster-ids>.

**Parameters** `cluster_ids` (`iterable[str]`) – The persistent IDs of the clusters to get version information for.

**Returns** A stream of the published clusters.

**Return type** Python generator yielding `PublishedCluster`

**record\_published\_cluster\_versions(record\_ids)**  
Retrieves version information for the published clusters of the given records. See <https://docs.tamr.com/reference#retrieve-published-clusters-given-record-ids>.

**Parameters** `record_ids` (`iterable[str]`) – The Tamr IDs of the records to get cluster version information for.

**Returns** A stream of the relevant published clusters.

**Return type** Python generator yielding `RecordPublishedCluster`

**estimate\_pairs()**  
Returns pair estimate information for a mastering project

**Returns** Pairs Estimate information.

**Return type** `EstimatedPairCounts`

**record\_clusters\_with\_data()**  
Project's unified dataset with associated clusters.

**Returns** The record clusters with data represented as a dataset

**Return type** `Dataset`

**published\_clusters\_with\_data()**  
Project's unified dataset with associated clusters.

**Returns** The published clusters with data represented as a dataset

**Return type** `Dataset`

**binning\_model()**  
Binning model for this project.

**Returns** Binning model for this project.

**Return type** `BinningModel`

**add\_input\_dataset(dataset)**  
Associate a dataset with a project in Tamr.

By default, datasets are not associated with any projects. They need to be added as input to a project before they can be used as part of that project

**Parameters** `dataset` (`Dataset`) – The dataset to associate with the project.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**as\_categorization()**  
Convert this project to a `CategorizationProject`

**Returns** This project.

**Return type** `CategorizationProject`

**Raises** `TypeError` – If the `type` of this project is not "CATEGORIZATION"

**as\_mastering()**  
Convert this project to a `MasteringProject`

**Returns** This project.

**Return type** `MasteringProject`

**Raises** `TypeError` – If the `type` of this project is not "DEDUP"

**attribute\_configurations()**  
Project's attribute's configurations.

**Returns** The configurations of the attributes of a project.

**Return type** `AttributeConfigurationCollection`

**attribute\_mappings()**  
Project's attribute's mappings.

**Returns** The attribute mappings of a project.

**Return type** `AttributeMappingCollection`

**property attributes**  
Attributes of this project.

**Returns** Attributes of this project.

**Return type** `AttributeCollection`

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

**property description**  
str

**Type** `type`

**property external\_id**  
str

**Type** `type`

**input\_datasets()**  
Retrieve a collection of this project's input datasets.

**Returns** The project's input datasets.

**Return type** `DatasetCollection`

```
property name
    str

    Type type

property relative_id
    str

    Type type

remove_input_dataset(dataset)
    Remove a dataset from a project.

    Parameters dataset (Dataset) – The dataset to be removed from this project.

    Returns HTTP response from the server

    Return type requests.Response

property resource_id
    str

    Type type

spec()
    Returns this project's spec.

    Returns The spec for the project.

    Return type ProjectSpec

property type
    //docs.tamr.com/reference#create-a-project.

    Type str

    Type A Tamr project type, listed in https

unified_dataset()
    Unified dataset for this project.

    Returns Unified dataset for this project.

    Return type Dataset
```

## Published Clusters

### Metric

```
class tamr_unify_client.mastering.published_cluster.metric.Metric(data)
    A metric for a published cluster.
```

This is not a *BaseResource* because it does not have its own API endpoint.

Parameters **data** – The JSON entity representing this cluster.

```
property name
```

str

Type type

```
property value
```

str

Type type

## Published Cluster

```
class tamr_unify_client.mastering.published_cluster.resource.PublishedCluster(data)
    A representation of a published cluster in a mastering project with version information. See https://docs.tamr.com/reference#retrieve-published-clusters-given-cluster-ids.
```

This is not a *BaseResource* because it does not have its own API endpoint.

**Parameters** `data` – The JSON entity representing this *PublishedCluster*.

**property** `id`  
str

**Type** type

**property** `versions`  
list[*PublishedClusterVersion*]  
**Type** type

## Published Cluster Configuration

```
class tamr_unify_client.mastering.published_cluster.configuration.PublishedClustersConfiguration
```

The configuration of published clusters in a project.

See <https://docs.tamr.com/reference#the-published-clusters-configuration-object>

**property** `relative_id`  
str

**Type** type

**property** `versions_time_to_live`  
str  
**Type** type

**spec()**  
Returns a spec representation of this published cluster configuration.

**Returns** The published cluster configuration spec.

**Return type** :class:`~tamr\_unify\_client.mastering.published\_cluster.configuration.PublishedClustersConfigurationSpec`

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** requests.Response

**property** `resource_id`  
str

**Type** type

## Published Cluster Version

```
class tamr_unify_client.mastering.published_cluster.version.PublishedClusterVersion(data)
    A version of a published cluster in a mastering project.

This is not a BaseResource because it does not have its own API endpoint.

Parameters data – The JSON entity representing this version.

property version
    str

        Type type

property timestamp
    str

        Type type

property name
    str

        Type type

property metrics
    list[Metric]

        Type type

property record_ids
    list[dict[str, str]]

        Type type
```

## Record Published Cluster

```
class tamr_unify_client.mastering.published_cluster.record.RecordPublishedCluster(data)
    A representation of a published cluster of a record in a mastering project with version information. See https://docs.tamr.com/reference#retrieve-published-clusters-given-record-ids.

This is not a BaseResource because it does not have its own API endpoint.

Parameters data – The JSON entity representing this RecordPublishedCluster.

property entity_id
    str

        Type type

property source_id
    str

        Type type

property origin_entity_id
    str

        Type type

property origin_source_id
    str

        Type type
```

```
property versions
list[RecordPublishedClusterVersion]
Type type
```

## Record Published Cluster Version

```
class tamr_unify_client.mastering.published_cluster.record_version.RecordPublishedClusterVersion
```

A version of a published cluster in a mastering project.

This is not a *BaseResource* because it does not have its own API endpoint.

**Parameters** `data` – The JSON entity representing this version.

```
property version
```

str

Type type

```
property timestamp
```

str

Type type

```
property cluster_id
```

str

Type type

### 3.1.8 Operation

```
class tamr_unify_client.operation.Operation(client, data, alias=None)
```

A long-running operation performed by Tamr. Operations appear on the “Jobs” page of the Tamr UI.

By design, client-side operations represent server-side operations *at a particular point in time* (namely, when the operation was fetched from the server). In other words: Operations *will not* pick up on server-side changes automatically. To get an up-to-date representation, refetch the operation e.g. `op = op.poll()`.

```
classmethod from_response(client, response)
```

Handle idiosyncrasies in constructing Operations from Tamr responses. When a Tamr API call would start an operation, but all results that would be produced by that operation are already up-to-date, Tamr returns *HTTP 204 No Content*

To make it easy for client code to handle these API responses without checking the response code, this method will either construct an Operation, or a dummy *NoOp* operation representing the 204 Success response.

#### Parameters

- `client` (`Client`) – Delegate underlying API calls to this client.
- `response` (`requests.Response`) – HTTP Response from the request that started the operation.

#### Returns Operation

**Return type** `Operation`

```
apply_options(asynchronous=False, **options)
```

Applies operation options to this operation.

**NOTE:** This function **should not** be called directly. Rather, options should be passed in through a higher-level function e.g. `refresh()`.

**Synchronous mode:** Automatically waits for operation to resolve before returning the operation.

**asynchronous mode:** Immediately return the 'PENDING' operation. It is up to the user to coordinate this operation with their code via `wait()` and/or `poll()`.

### Parameters

- **asynchronous** (`bool`) – Whether or not to run in asynchronous mode. Default: `False`.
- **\*\*options** – When running in synchronous mode, these options are passed to the underlying `wait()` call.

**Returns** Operation with options applied.

**Return type** `Operation`

#### `property type`

`str`

**Type** `type`

#### `property description`

`str`

**Type** `type`

#### `property state`

Server-side state of this operation.

Operation state can be unresolved (i.e. `state` is one of: 'PENDING', 'RUNNING'), or resolved (i.e. `state` is one of: 'CANCELED', 'SUCCEEDED', 'FAILED'). Unless opting into asynchronous mode, all exposed operations should be resolved.

Note: you only need to manually pick up server-side changes when opting into asynchronous mode when kicking off this operation.

### Usage:

```
>>> op.state # operation is currently 'PENDING'
'PENDING'
>>> op.wait() # continually polls until operation resolves
>>> op.state # incorrect usage; operation object state never changes.
'PENDING'
>>> op = op.poll() # correct usage; use value returned by Operation.poll_
→or Operation.wait
>>> op.state
'SUCCEEDED'
```

#### `poll()`

Poll this operation for server-side updates.

Does not update the calling `Operation` object. Instead, returns a new `Operation`.

**Returns** Updated representation of this operation.

**Return type** `Operation`

#### `wait(poll_interval_seconds=3, timeout_seconds=None)`

Continuously polls for this operation's server-side state.

### Parameters

- **poll\_interval\_seconds** (`int`) – Time interval (in seconds) between subsequent polls.
- **timeout\_seconds** (`int`) – Time (in seconds) to wait for operation to resolve.

**Raises** `TimeoutError` – If operation takes longer than `timeout_seconds` to resolve.

**Returns** Resolved operation.

**Return type** `Operation`

### `succeeded()`

Convenience method for checking if operation was successful.

**Returns** True if operation's state is 'SUCCEEDED', False otherwise.

**Return type** `bool`

### `delete()`

Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

**Return type** `requests.Response`

### `property relative_id`

str

**Type** `type`

### `property resource_id`

str

**Type** `type`

## 3.1.9 Projects

### Attribute Configurations

#### Attribute Configuration

```
class tamr_unify_client.project.attribute_configuration.resource.AttributeConfiguration(client)
```

The configurations of Tamr Attributes.

See <https://docs.tamr.com/reference#the-attribute-configuration-object>

### `property relative_id`

str

**Type** `type`

### `property id`

str

**Type** `type`

### `property relative_attribute_id`

str

**Type** `type`

---

```

property attribute_role
    str

    Type type

property similarity_function
    str

    Type type

property enabled_for_ml
    bool

    Type type

property tokenizer
    str

    Type type

property numeric_field_resolution
    list

    Type type

property attribute_name
    str

    Type type

spec()
    Returns this attribute configuration's spec.

    Returns The spec of this attribute configuration.

    Return type AttributeConfigurationSpec

delete()
    Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

    Returns HTTP response from the server

    Return type requests.Response

property resource_id
    str

    Type type

```

## Attribute Configuration Spec

```
class tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
```

A representation of the server view of an attribute configuration.

```
static of(resource)
    Creates an attribute configuration spec from an attribute configuration.
```

**Parameters** **resource** (AttributeConfiguration) – The existing attribute configuration.

**Returns** The corresponding attribute creation spec.

**Return type** AttributeConfigurationSpec

**static new()**

Creates a blank spec that could be used to construct a new attribute configuration.

**Returns** The empty spec.

**Return type** `AttributeConfigurationSpec`

**from\_data**(*data*)

Creates a spec with the same client and API path as this one, but new data.

**Parameters** `data`(*dict*) – The data for the new spec.

**Returns** The new spec.

**Return type** `AttributeConfigurationSpec`

**to\_dict()**

Returns a version of this spec that conforms to the API representation.

**Returns** The spec's dict.

**Return type** `dict`

**with\_attribute\_role**(*new\_attribute\_role*)

Creates a new spec with the same properties, updating attribute role.

**Parameters** `new_attribute_role`(*str*) – The new attribute role.

**Returns** A new spec.

**Return type** `AttributeConfigurationSpec`

**with\_similarity\_function**(*new\_similarity\_function*)

Creates a new spec with the same properties, updating similarity function.

**Parameters** `new_similarity_function`(*str*) – The new similarity function.

**Returns** A new spec.

**Return type** `AttributeConfigurationSpec`

**with\_enabled\_for\_ml**(*new\_enabled\_for\_ml*)

Creates a new spec with the same properties, updating enabled for ML.

**Parameters** `new_enabled_for_ml`(*bool*) – Whether the builder is enabled for ML.

**Returns** A new spec.

**Return type** `AttributeConfigurationSpec`

**with\_tokenizer**(*new\_tokenizer*)

Creates a new spec with the same properties, updating tokenizer.

**Parameters** `new_tokenizer`(*str*) – The new tokenizer.

**Returns** A new spec.

**Return type** `AttributeConfigurationSpec`

**with\_numeric\_field\_resolution**(*new\_numeric\_field\_resolution*)

Creates a new spec with the same properties, updating numeric field resolution.

**Parameters** `new_numeric_field_resolution`(*str*) – The new numeric field resolution.

**Returns** A new spec.

**Return type** `AttributeConfigurationSpec`

---

```
with_attribute_name(new_attribute_name)
Creates a new spec with the same properties, updating new attribute name.

Parameters new_attribute_name (str) – The new attribute name.

Returns A new spec.

Return type AttributeConfigurationSpec
```

```
put()
Updates the attribute configuration on the server.

Returns The modified attribute configuration.

Return type AttributeConfiguration
```

## Attribute Configuration Collection

```
class tamr_unify_client.project.attribute_configuration.collection.AttributeConfigurationCollection
```

Collection of *AttributeConfiguration*

**Parameters**

- **client** (*Client*) – Client for API call delegation.
- **api\_path** (*str*) – API path used to access this collection. E.g. "projects/1/attributeConfigurations"

```
by_resource_id(resource_id)
Retrieve an attribute configuration by resource ID.

Parameters resource_id (str) – The resource ID.

Returns The specified attribute configuration.

Return type AttributeConfiguration
```

```
by_relative_id(relative_id)
Retrieve an attribute configuration by relative ID.

Parameters relative_id (str) – The relative ID.

Returns The specified attribute configuration.

Return type AttributeConfiguration
```

```
by_external_id(external_id)
Retrieve an attribute configuration by external ID.

Since attributes do not have external IDs, this method is not supported and will raise a NotImplementedError.
```

**Parameters** **external\_id** (*str*) – The external ID.

**Returns** The specified attribute, if found.

**Return type** *AttributeConfiguration*

**Raises**

- **KeyError** – If no attribute with the specified external\_id is found
- **LookupError** – If multiple attributes with the specified external\_id are found
- **NotImplementedError** – AttributeConfiguration does not support external\_id

**stream()**

Stream attribute configurations in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of attribute configurations.

**Return type** Python generator yielding *AttributeConfiguration*

**Usage:**

```
>>> for attributeConfiguration in collection.stream(): # explicit
>>>     do_stuff(attributeConfiguration)
>>> for attributeConfiguration in collection: # implicit
>>>     do_stuff(attributeConfiguration)
```

**create(*creation\_spec*)**

Create an Attribute configuration in this collection

**Parameters** *creation\_spec* (*dict[str, str]*) – Attribute configuration creation specification should be formatted as specified in the [Public Docs](#) for adding an *AttributeConfiguration*.

**Returns** The created Attribute configuration

**Return type** *AttributeConfiguration*

**delete\_by\_resource\_id(*resource\_id*)**

Deletes a resource from this collection by resource ID.

**Parameters** *resource\_id* (*str*) – The resource ID of the resource that will be deleted.

**Returns** HTTP response from the server.

**Return type** *requests.Response*

## Attribute Mappings

### Attribute Mapping

```
class tamr_unify_client.project.attribute_mapping.resource.AttributeMapping(client,
                                                                           data)
see https://docs.tamr.com/reference#retrieve-projects-mappings AttributeMapping and AttributeMappingCollection do not inherit from BaseResource and BaseCollection. BC and BR require a specific URL for each individual attribute mapping (ex: /projects/1/attributeMappings/1), but these types of URLs do not exist for attribute mappings
```

**property id**  
str

**Type** *type*

**property relative\_id**  
str

**Type** *type*

**property input\_attribute\_id**  
str

**Type** *type*

```
property relative_input_attribute_id
    str

    Type type

property input_dataset_name
    str

    Type type

property input_attribute_name
    str

    Type type

property unified_attribute_id
    str

    Type type

property relative_unified_attribute_id
    str

    Type type

property unified_dataset_name
    str

    Type type

property unified_attribute_name
    str

    Type type

property resource_id
    str

    Type type

spec()
    Returns a spec representation of this attribute mapping.

    Returns The attribute mapping spec.

    Return type AttributeMappingSpec

delete()
    Delete this attribute mapping.

    Returns HTTP response from the server

    Return type requests.Response
```

## Attribute Mapping Spec

```
class tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec(data)
    A representation of the server view of an attribute mapping

    static of(resource)
        Creates an attribute mapping spec from a attribute mapping.

        Parameters resource (AttributeMapping) – The existing attribute mapping.

        Returns The corresponding attribute mapping spec.

        Return type AttributeMappingSpec

    static new()
        Creates a blank spec that could be used to construct a new attribute mapping.

        Returns The empty spec.

        Return type AttributeMappingSpec

    to_dict()
        Returns a version of this spec that conforms to the API representation.

        Returns The spec's dict.

        Return type dict

    with_input_attribute_id(new_input_attribute_id)
        Creates a new spec with the same properties, updating the input attribute id.

        Parameters new_input_attribute_id (str) – The new input attribute id.

        Returns The new spec.

        Return type AttributeMappingSpec

    with_relative_input_attribute_id(new_relative_input_attribute_id)
        Creates a new spec with the same properties, updating the relative input attribute id.

        Parameters new_relative_input_attribute_id (str) – The new relative input attribute Id.

        Returns The new spec.

        Return type AttributeMappingSpec

    with_input_dataset_name(new_input_dataset_name)
        Creates a new spec with the same properties, updating the input dataset name.

        Parameters new_input_dataset_name (str) – The new input dataset name.

        Returns The new spec.

        Return type AttributeMappingSpec

    with_input_attribute_name(new_input_attribute_name)
        Creates a new spec with the same properties, updating the input attribute name.

        Parameters new_input_attribute_name (str) – The new input attribute name.

        Returns The new spec.

        Return type AttributeMappingSpec

    with_unified_attribute_id(new_unified_attribute_id)
        Creates a new spec with the same properties, updating the unified attribute id.
```

---

**Parameters** `new_unified_attribute_id(str)` – The new unified attribute id.

**Returns** The new spec.

**Return type** `AttributeMappingSpec`

**with\_relative\_unified\_attribute\_id(new\_relative\_unified\_attribute\_id)**  
Creates a new spec with the same properties, updating the relative unified attribute id.

**Parameters** `new_relative_unified_attribute_id(str)` – The new relative unified attribute id.

**Returns** The new spec.

**Return type** `AttributeMappingSpec`

**with\_unified\_dataset\_name(new\_unified\_dataset\_name)**  
Creates a new spec with the same properties, updating the unified dataset name.

**Parameters** `new_unified_dataset_name(str)` – The new unified dataset name.

**Returns** The new spec.

**Return type** `AttributeMappingSpec`

**with\_unified\_attribute\_name(new\_unified\_attribute\_name)**  
Creates a new spec with the same properties, updating the unified attribute name.

**Parameters** `new_unified_attribute_name(str)` – The new unified attribute name.

**Returns** The new spec.

**Return type** `AttributeMappingSpec`

## Attribute Mapping Collection

```
class tamr_unify_client.project.attribute_mapping.collection.AttributeMappingCollection(client, api)
    Collection of AttributeMapping
```

**Parameters**

- `client(Client)` – Client for API call delegation.
- `api_path(str)` – API path used to access this collection.

**stream()**  
Stream attribute mappings in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of attribute mappings.

**Return type** Python generator yielding `AttributeMapping`

**by\_resource\_id(resource\_id)**  
Retrieve an item in this collection by resource ID.

**Parameters** `resource_id(str)` – The resource ID.

**Returns** The specified attribute mapping.

**Return type** `AttributeMapping`

**by\_relative\_id(relative\_id)**  
Retrieve an item in this collection by relative ID.

**Parameters** `relative_id(str)` – The relative ID.

**Returns** The specified attribute mapping.

**Return type** `AttributeMapping`

**create**(*creation\_spec*)

Create an Attribute mapping in this collection

**Parameters** `creation_spec (dict[str, str])` – Attribute mapping creation specification should be formatted as specified in the [Public Docs](#) for adding an `AttributeMapping`.

**Returns** The created Attribute mapping

**Return type** `AttributeMapping`

**delete\_by\_resource\_id**(*resource\_id*)

Delete an attribute mapping using its Resource ID.

**Parameters** `resource_id (str)` – the resource ID of the mapping to be deleted.

**Returns** HTTP response from the server

**Return type** `requests.Response`

## Project

**class** `tamr_unify_client.project.resource.Project`(*client, data, alias=None*)

A Tamr project.

**property name**

`str`

**Type** `type`

**property external\_id**

`str`

**Type** `type`

**property description**

`str`

**Type** `type`

**property type**

`//docs.tamr.com/reference#create-a-project.`

**Type** `str`

**Type** A Tamr project type, listed in <https://docs.tamr.com/reference#create-a-project>

**property attributes**

Attributes of this project.

**Returns** Attributes of this project.

**Return type** `AttributeCollection`

**unified\_dataset()**

Unified dataset for this project.

**Returns** Unified dataset for this project.

**Return type** `Dataset`

**as\_categorization()**

Convert this project to a `CategorizationProject`

**Returns** This project.

**Return type** *CategorizationProject*

**Raises** `TypeError` – If the `type` of this project is not "CATEGORIZATION"

**as\_mastering()**  
Convert this project to a *MasteringProject*

**Returns** This project.

**Return type** *MasteringProject*

**Raises** `TypeError` – If the `type` of this project is not "DEDUP"

**add\_input\_dataset(dataset)**  
Associate a dataset with a project in Tamr.

By default, datasets are not associated with any projects. They need to be added as input to a project before they can be used as part of that project

**Parameters** `dataset` (*Dataset*) – The dataset to associate with the project.

**Returns** HTTP response from the server

**Return type** *requests.Response*

**remove\_input\_dataset(dataset)**  
Remove a dataset from a project.

**Parameters** `dataset` (*Dataset*) – The dataset to be removed from this project.

**Returns** HTTP response from the server

**Return type** *requests.Response*

**input\_datasets()**  
Retrieve a collection of this project's input datasets.

**Returns** The project's input datasets.

**Return type** *DatasetCollection*

**attribute\_configurations()**  
Project's attribute's configurations.

**Returns** The configurations of the attributes of a project.

**Return type** *AttributeConfigurationCollection*

**attribute\_mappings()**  
Project's attribute's mappings.

**Returns** The attribute mappings of a project.

**Return type** *AttributeMappingCollection*

**spec()**  
Returns this project's spec.

**Returns** The spec for the project.

**Return type** *ProjectSpec*

**delete()**  
Deletes this resource. Some resources do not support deletion, and will raise a 405 error if this is called.

**Returns** HTTP response from the server

```
    Return type requests.Response  
property relative_id  
        str  
            Type type  
property resource_id  
        str  
            Type type
```

## Project Spec

```
class tamr_unify_client.project.resource.ProjectSpec(client, data, api_path)
```

A representation of the server view of a project.

```
    static of(resource)
```

Creates a project spec from a project.

**Parameters** resource (*Project*) – The existing project.

**Returns** The corresponding project spec.

**Return type** ProjectSpec

```
    static new()
```

Creates a blank spec that could be used to construct a new project.

**Returns** The empty spec.

**Return type** ProjectSpec

```
    from_data(data)
```

Creates a spec with the same client and API path as this one, but new data.

**Parameters** data (*dict*) – The data for the new spec.

**Returns** The new spec.

**Return type** ProjectSpec

```
    to_dict()
```

Returns a version of this spec that conforms to the API representation.

**Returns** The spec's dict.

**Return type** dict

```
    with_name(new_name)
```

Creates a new spec with the same properties, updating name.

**Parameters** new\_name (*str*) – The new name.

**Returns** The new spec.

**Return type** ProjectSpec

```
    with_description(new_description)
```

Creates a new spec with the same properties, updating description.

**Parameters** new\_description (*str*) – The new description.

**Returns** The new spec.

**Return type** ProjectSpec

**with\_type** (*new\_type*)

Creates a new spec with the same properties, updating type.

**Parameters** `new_type` (*str*) – The new type.

**Returns** The new spec.

**Return type** *ProjectSpec*

**with\_external\_id** (*new\_external\_id*)

Creates a new spec with the same properties, updating external ID.

**Parameters** `new_external_id` (*str*) – The new external ID.

**Returns** The new spec.

**Return type** *ProjectSpec*

**with\_unified\_dataset\_name** (*new\_unified\_dataset\_name*)

Creates a new spec with the same properties, updating unified dataset name.

**Parameters** `new_unified_dataset_name` (*str*) – The new unified dataset name.

**Returns** The new spec.

**Return type** *ProjectSpec*

**put()**

Commits these changes by updating the project in Tamr.

**Returns** The updated project.

**Return type** *Project*

## Project Collection

```
class tamr_unify_client.project.collection.ProjectCollection(client,
                                                               api_path='projects')
```

Collection of *Project* s.

### Parameters

- `client` (*Client*) – Client for API call delegation.
- `api_path` (*str*) – API path used to access this collection. Default: "projects".

**by\_resource\_id** (*resource\_id*)

Retrieve a project by resource ID.

**Parameters** `resource_id` (*str*) – The resource ID. E.g. "1"

**Returns** The specified project.

**Return type** *Project*

**by\_relative\_id** (*relative\_id*)

Retrieve a project by relative ID.

**Parameters** `relative_id` (*str*) – The resource ID. E.g. "projects/1"

**Returns** The specified project.

**Return type** *Project*

**by\_external\_id** (*external\_id*)

Retrieve a project by external ID.

**Parameters** `external_id`(*str*) – The external ID.

**Returns** The specified project, if found.

**Return type** *Project*

**Raises**

- **KeyError** – If no project with the specified external\_id is found
- **LookupError** – If multiple projects with the specified external\_id are found

**stream()**

Stream projects in this collection. Implicitly called when iterating over this collection.

**Returns** Stream of projects.

**Return type** Python generator yielding *Project*

**Usage:**

```
>>> for project in collection.stream(): # explicit
>>>     do_stuff(project)
>>> for project in collection: # implicit
>>>     do_stuff(project)
```

**by\_name**(*project\_name*)

Get project by name

Fetches a specific project in this collection by exact-match on name.

**Parameters** `project_name`(*str*) – Name of the desired project.

**Raises** **KeyError** – If no project with specified name was found.

**Return type** *Project*

**create**(*creation\_spec*)

Create a Project in Tamr

**Parameters** `creation_spec`(*dict*[*str*, *str*]) – Project creation specification should be formatted as specified in the [Public Docs for Creating a Project](#).

**Returns** The created Project

**Return type** *Project*

**delete\_by\_resource\_id**(*resource\_id*)

Deletes a resource from this collection by resource ID.

**Parameters** `resource_id`(*str*) – The resource ID of the resource that will be deleted.

**Returns** HTTP response from the server.

**Return type** `requests.Response`

## Project Step

```
class tamr_unify_client.project.step.ProjectStep(client, data)
```

A step of a Tamr project. This is not a *BaseResource* because it has no API path and cannot be directly retrieved or modified.

See <https://docs.tamr.com/reference#retrieve-downstream-dataset-usage>

### Parameters

- **client** (*Client*) – Delegate underlying API calls to this client.
- **data** (*dict*) – The JSON body containing project step information.

```
property project_step_id
```

str

Type *type*

```
property project_step_name
```

str

Type *type*

```
property project_name
```

str

Type *type*

```
property type
```

//docs.tamr.com/reference#create-a-project.

Type str

Type A Tamr project type, listed in https

```
project()
```

Retrieves the *Project* this step is associated with.

**Returns** This step's project.

**Return type** *Project*

### Raises

- **KeyError** – If no project with the specified name is found.
- **LookupError** – If multiple projects with the specified name are found.



## CONTRIBUTOR GUIDE

### 4.1 Contributor guide

Thank you for learning how to contribute to Tamr's Python Client! Your contribution will help you and many others in the Tamr community. Before you begin, make sure you are viewing the [latest version of Contributor Guide](#).

#### 4.1.1 Feedback

Before submitting a new issue, [you can search existing issues](#). If the bug/feature has been submitted already, leave a like on the description of the Github Issue. Maintainers will consider number of likes when prioritizing issues.

##### Bug reports

Submit bug reports as [Github issues](#).

##### Feature requests

Submit feature requests as [Github issues](#).

#### 4.1.2 Documentation

##### How to write docs

Before you begin to add content, decide which of the three types of content you want to add:

1. Tutorial
2. How-To guide
3. Explanation

---

**Note:** There is fourth type of content, known as Reference.

For the Tamr Client, you don't need to add reference topics manually because reference documentation for the Tamr Client is generated automatically based on the source code.

For more details, see Reference description below.

---

For more information about each type of content, see the following descriptions. Also see [Divio's documentation system manual](#).

## **Tutorial**

Tutorials are learning-oriented and ...

- Must include an end-to-end walkthrough for a specific use case, such as “Tutorial: Deduplicating buildings in Cambridge”.
- Must have a clearly stated goal and allow the users to achieve it after they complete the steps in the tutorial.
- Must provide the sample data and input configuration that are necessary for the user to complete the tutorial. Include this information upfront, at the start of your tutorial.
- Must be self-contained, but can include links to procedures described elsewhere in this documentation.

Tutorials are useful if the use case is both simple and in high demand. Not every use case deserves a tutorial. Before writing a tutorial, think first of a use case that has a high learning value, and then prepare the assets needed to complete your tutorial, such as a sample dataset and sample configuration.

Tutorials are in high demand. If you write a good one, many users will reference it and thank you for your work!

## **How-To**

How-Tos are task-oriented and ...

- Must include a list of numbered steps, known as a task, or a procedure, to help users complete a specific, domain-agnostic task, such as running a request, copying a file, installing, exporting, or other. For example, you can create a task titled “How to stream datasets out of Tamr”.
- Must include a context paragraph, such as “It is often useful to stream datasets from Tamr, to load them into business analytics applications, such as Tableau, for analysis.” Context may also include checks needed to be in place before users start the task, and links to related concepts. Context must provide information needed to begin the task, such as, it can list the host and port URL at which the endpoint for the service is served.
- Must include a stem sentence, such as: “To stream a dataset out of Tamr:” The stem sentence is followed by numbered steps.
- Must include a numbered list of steps where each step must begin with an imperative verb, such as: “Run the following curl request.”, or “Save the file”. For more examples see [Use Imperatives in Procedures](#).

## **Explanation**

Explanations are understanding-oriented and ...

- Must explain a single concept of the Tamr Python client. If you'd like to write another concept, create it separately.
- Must [keep sentences short](#).
- May include examples of code or text examples.

## Reference

Reference is information-oriented.

It is something that users cannot remember and want to be able to refer to, often. Reference provides details, such as configuration parameters for a particular method or call. It never contains tasks, or concepts. Reference is often automatically-generated from code, to ensure it is up-to-date and accurate at all times.

---

**Note:** Our reference documentation is automatically generated by [autodoc](<https://www.sphinx-doc.org/en/master/usage/extensions/autodoc.html>) based on type annotations and docstrings in the source code.

---

### 4.1.3 Code

#### Installation

#### Pre-requisites

1. Install build dependencies for pyenv
2. Install pyenv
3. Install poetry

#### Clone + install

1. Clone your fork and cd into the project:

```
git clone https://github.com/<your-github-username>/tamr-client
cd tamr-client
```

2. Install all Python versions in .python-version:

Dev tasks will use these Python versions.

```
# run `pyenv install` for each line in `.python-version`
cat .python-version | xargs -L 1 pyenv install
```

3. Install project dependencies via poetry:

```
poetry install
```

#### Run dev tasks

This project uses nox.

Since nox will be running inside of a poetry environment (to guarantee you are running the same version of nox as everyone else), we recommend adding the following alias to your .bashrc / .zshrc to save you some keystrokes:

```
alias prn='poetry run nox'
```

To run all checks:

```
prn # with alias  
poetry run nox # without alias
```

## Linting

To run linter:

```
prn -s lint # with alias  
poetry run nox -s lint # without alias
```

## Formatting

To run formatter:

```
prn -s format # with alias  
poetry run nox -s format # without alias
```

Run the formatter with the `--fix` flag to autofix formatting:

```
prn -s format -- --fix # with alias  
poetry run nox -s format -- --fix # without alias
```

## Typechecks

To run typechecks:

```
prn -s typecheck # with alias  
poetry run nox -s typecheck # without alias
```

## Tests

To run all tests:

```
prn -s test # with alias  
poetry run nox -s test # without alias
```

---

To run tests for a specific Python version e.g. 3.6:

```
prn -s test-3.6 # with alias  
poetry run nox -s test-3.6 # without alias
```

---

See `nox --list` for more details.

---

To run specific tests, see [these pytest docs](#) and pass `pytest` args after `--` e.g.:

```
prn -s test -- tests/unit/test_attribute.py
```

## Docs

To build the docs:

```
prn -s docs # with alias  
poetry run nox -s docs # without alias
```

After docs are build, view them by:

```
open -a 'firefox' docs/_build/index.html # open in Firefox  
open -a 'Google Chrome' docs/_build/index.html # open in Chrome
```

## Configure your Text Editor

### Atom

### VS Code

### Style Guide

### Formatting

Code should generally conform to the [PEP8 style guidelines](#).

- [Flake8](#) is a linter to help check that code is aligned with these formatting requirements
- [Black](#) is a formatter that can be used to automatically reformat code to resolve many (but not all) formatting issues
- For details on using these tools, see [the dev tasks guide](#)

### Structure

- Classes with methods should be avoided in favor of simple [dataclasses](#) and functions
- Types (i.e. [dataclasses](#)) should be within the `_types` package. Separating types and functions into different packages helps keep type resolution simple so that all of our tools (`mypy`, `sphinx`, `pytest`) run correctly.

### Google-style docstrings

All functions and class definitions should use [Google-style docstrings](#) and be annotated with [type hints](#).

## Internal Imports

When importing from within `tamr-client`:

- Use import statements for modules, classes, and exceptions
- Never import functions directly. Instead import the containing module and use `module.function`
- Use `from foo import bar` instead of `import foo.bar as bar`

## Contributing pull requests

### RFCs

If the proposed changes require design input, open a Request For Comment issue.

Discuss the feature with project maintainers to be sure that your change fits with the project vision and that you won't be wasting effort going in the wrong direction.

Once you get the green light from maintainers, you can proceed with the PR.

### Pull requests

Contributions / PRs should follow the [Forking Workflow](#). In short:

1. Fork it: [https://github.com/\[your-github-username\]/tamr-client/fork](https://github.com/[your-github-username]/tamr-client/fork)
2. Create your feature branch:

```
git checkout -b my-new-feature
```

3. Commit your changes:

```
git commit -am 'Add some feature'
```

4. Push to the branch:

```
git push origin my-new-feature
```

5. Create a new Pull Request

### Commits

Split and squash commits as necessary to create a clean `git` history. Once you ask for review, only add new commits (do not change existing commits) for reviewer convenience. You may change commits in your PR only if reviewers are ok with it.

Also, write [good commit messages!](#)

## CI checks

Continuous integration (CI) checks are run automatically for all pull requests. CI runs the same [dev tasks](#) that you can run locally.

You should run dev tasks locally *before* submitting your PR to cut down on subsequent commits to fix the CI checks.

### 4.1.4 Maintainers

Maintainer responsibilities:

- Triage issues
- Review + merge pull requests
- Discuss RFCs
- Publish new releases

Current maintainers:

Want to become a maintainer? Open a pull request that adds your name to the list of current maintainers!



## 5.1 BETA

**WARNING:** Do not rely on BETA features in production workflows. Support from Tamr may be limited.

### 5.1.1 Reference

#### Attribute

#### Attribute

```
class tamr_client.Attribute(url, name, type, is_nullable, description=None)
```

A Tamr Attribute.

See <https://docs.tamr.com/reference#attribute-types>

##### Parameters

- **url** (URL) –
- **name** (str) –
- **type** (Union[PrimitiveType, Array, Map, Record]) –
- **is\_nullable** (bool) –
- **description** (Optional[str]) –

```
tamr_client.attribute.from_resource_id(session, dataset, id)
```

Get attribute by resource ID

Fetches attribute from Tamr server

##### Parameters

- **dataset** (Dataset) – Dataset containing this attribute
- **id** (str) – Attribute ID

##### Raises

- **attribute.NotFound** – If no attribute could be found at the specified URL. Corresponds to a 404 HTTP error.
- **requests.HTTPError** – If any other HTTP error is encountered.

**Return type** Attribute

```
tamr_client.attribute.from_dataset_all(session, dataset)
```

Get all attributes from a dataset

**Parameters** **dataset** (Dataset) – Dataset containing the desired attributes

**Return type** Tuple[Attribute, ...]

**Returns** The attributes for the specified dataset

**Raises** [requests.HTTPError](#) – If an HTTP error is encountered.

```
tamr_client.attribute.to_json(attr)
```

Serialize attribute into JSON

**Parameters** **attr** (Attribute) – Attribute to serialize

**Return type** Dict[str, Any]

**Returns** JSON data representing the attribute

```
tamr_client.attribute.create(session, dataset, *, name, is_nullable,
                             type=Array(inner_type=<PrimitiveType.STRING: 5>), description=None)
```

Create an attribute

Posts a creation request to the Tamr server

**Parameters**

- **dataset** (Dataset) – Dataset that should contain the new attribute
- **name** (str) – Name for the new attribute
- **type** (Union[PrimitiveType, Array, Map, Record]) – Attribute type for the new attribute
- **is\_nullable** (bool) – Determines if the new attribute can contain NULL values
- **description** (Optional[str]) – Description of the new attribute
- **force** – If *True*, skips reserved attribute name check

**Return type** Attribute

**Returns** The newly created attribute

**Raises**

- **ReservedName** – If attribute name is reserved.
- **AlreadyExists** – If an attribute already exists at the specified URL. Corresponds to a 409 HTTP error.
- [requests.HTTPError](#) – If any other HTTP error is encountered.

```
tamr_client.attribute.update(session, attribute, *, description=None)
```

Update an existing attribute

PUTS an update request to the Tamr server

**Parameters**

- **attribute** (Attribute) – Existing attribute to update
- **description** (Optional[str]) – Updated description for the existing attribute

**Return type** Attribute

**Returns** The newly updated attribute

**Raises**

- `attribute.NotFound` – If no attribute could be found at the specified URL. Corresponds to a 404 HTTP error.
- `requests.HTTPError` – If any other HTTP error is encountered.

```
tamr_client.attribute.delete(session, attribute)
```

Deletes an existing attribute

Sends a deletion request to the Tamr server

**Parameters** `attribute` (Attribute) – Existing attribute to delete

**Raises**

- `attribute.NotFound` – If no attribute could be found at the specified URL. Corresponds to a 404 HTTP error.
- `requests.HTTPError` – If any other HTTP error is encountered.

**Exceptions**

```
class tamr_client.attribute.AlreadyExists
```

Raised when trying to create an attribute that already exists on the server

```
class tamr_client.attribute.NotFound
```

Raised when referencing (e.g. updating or deleting) an attribute that does not exist on the server.

```
class tamr_client.attribute.ReservedName
```

Raised when attempting to create an attribute with a reserved name

**AttributeType**

See <https://docs.tamr.com/reference#attribute-types>

```
tamr_client.attribute.type.BOOLEAN = <PrimitiveType.BOOLEAN: 1>
```

An enumeration.

```
tamr_client.attribute.type.DOUBLE = <PrimitiveType.DOUBLE: 2>
```

An enumeration.

```
tamr_client.attribute.type.INT = <PrimitiveType.INT: 3>
```

An enumeration.

```
tamr_client.attribute.type.LONG = <PrimitiveType.LONG: 4>
```

An enumeration.

```
tamr_client.attribute.type.STRING = <PrimitiveType.STRING: 5>
```

An enumeration.

```
tamr_client.attribute.type.DEFAULT = Array(inner_type=<PrimitiveType.STRING: 5>)
//docs.tamr.com/reference#attribute-types
```

---

**Note:** `sphinx_autodoc_typehints` cannot handle forward reference to `AttributeType`, so reference docs are written manually for this type

---

**Parameters** `inner_type` –

**Type** See <https://docs.tamr.com/reference#attribute-types>

```
tamr_client.attribute.type.GEOSPATIAL = Record(attributes=(SubAttribute(name='point', type=
```

//docs.tamr.com/reference#attribute-types

**Parameters attributes** –

**Type** See <https://docs.tamr.com/reference#attribute-types>

```
class tamr_client.attribute.type.Array(inner_type)
```

**Parameters inner\_type** (AttributeType) –

```
class tamr_client.attribute.type.Map(inner_type)
```

**Parameters inner\_type** (AttributeType) –

```
class tamr_client.attribute.type.Record(attributes)
```

See <https://docs.tamr.com/reference#attribute-types>

**Parameters attributes** (Tuple[SubAttribute, ...]) –

```
tamr_client.attribute.type.from_json(data)
```

Make an attribute type from JSON data (deserialize)

**Parameters data** (Dict[str, Any]) – JSON data from Tamr server

**Return type** Union[PrimitiveType, Array, Map, Record]

```
tamr_client.attribute.type.to_json(attr_type)
```

Serialize attribute type to JSON

**Parameters attr\_type** (Union[PrimitiveType, Array, Map, Record]) – Attribute type to serialize

**Return type** Dict[str, Any]

## SubAttribute

```
class tamr_client.SubAttribute(name, type, is_nullable, description=None)
```

**Parameters**

- **name** (str) –
- **type** (AttributeType) –
- **is\_nullable** (bool) –
- **description** (Optional [str]) –

```
tamr_client.attribute.sub.from_json(data)
```

Make a SubAttribute from JSON data (deserialize)

**Parameters data** (Dict[str, Any]) – JSON data received from Tamr server.

**Return type** SubAttribute

```
tamr_client.attribute.sub.to_json(subattr)
```

Serialize subattribute into JSON

**Parameters subattr** (SubAttribute) – SubAttribute to serialize

**Return type** Dict[str, Any]

## Auth

```
class tamr_client.UsernamePasswordAuth(username, password)
```

Provides username/password authentication for Tamr.

Sets the *Authorization* HTTP header with Tamr's custom *BasicCreds* format.

### Parameters

- **username** (`str`) –
- **password** (`str`) –

### Example

```
>>> import tamr_client as tc
>>> auth = tc.UsernamePasswordAuth('my username', 'my password')
>>> s = tc.Session(auth)
```

## Dataset

### Dataset

```
class tamr_client.Dataset(url, name, key_attribute_names, description=None)
```

A Tamr dataset

See <https://docs.tamr.com/reference/dataset-models>

### Parameters

- **url** (URL) – The canonical dataset-based URL for this dataset e.g. */datasets/1*
- **name** (`str`) –
- **key\_attribute\_names** (`Tuple[str, ...]`) –
- **description** (`Optional[str]`) –

`tamr_client.dataset.from_resource_id(session, instance, id)`

Get dataset by resource ID

Fetches dataset from Tamr server

### Parameters

- **instance** (`Instance`) – Tamr instance containing this dataset
- **id** (`str`) – Dataset ID

### Raises

- `dataset.NotFound` – If no dataset could be found at the specified URL. Corresponds to a 404 HTTP error.
- `requests.HTTPError` – If any other HTTP error is encountered.

**Return type** Dataset

## Exceptions

```
class tamr_client.dataset.NotFound
```

Raised when referencing (e.g. updating or deleting) a dataset that does not exist on the server.

## Record

See <https://docs.tamr.com/reference/record> “The recommended approach for modifying records is to use the `upsert()` and `delete()` functions for all use cases they can handle. For more advanced use cases, the underlying `_update()` function can be used directly.”

```
record.upsert(session, dataset, records, *, primary_key_name=None)
```

Create or update the specified records.

### Parameters

- **dataset** (`Dataset`) – Dataset to receive record updates
- **records** (`Iterable[Dict]`) – The records to update, as dictionaries
- **primary\_key\_name** (`Optional[str]`) – The primary key for these records, which must be a key in each record dictionary. By default the `key_attribute_name` of dataset

**Return type** `Dict[str, Any]`

**Returns** JSON response body from server

### Raises

- `requests.HTTPError` – If an HTTP error is encountered
- `primary_key.NotFound` – If `primary_key_name` does not match dataset primary key
- `primary_key.NotFound` – If `primary_key_name` not in a record dictionary

```
record.delete(session, dataset, records, *, primary_key_name=None)
```

Deletes the specified records, based on primary key values. Does not check that other attribute values match.

### Parameters

- **dataset** (`Dataset`) – Dataset from which to delete records
- **records** (`Iterable[Dict]`) – The records to update, as dictionaries
- **primary\_key\_name** (`Optional[str]`) – The primary key for these records, which must be a key in each record dictionary. By default the `key_attribute_name` of dataset

**Return type** `Dict[str, Any]`

**Returns** JSON response body from server

### Raises

- `requests.HTTPError` – If an HTTP error is encountered
- `primary_key.NotFound` – If `primary_key_name` does not match dataset primary key
- `primary_key.NotFound` – If `primary_key_name` not in a record dictionary

```
record._update(session, dataset, updates)
```

Send a batch of record creations/updates/deletions to this dataset. You probably want to use `upsert()` or `delete()` instead.

### Parameters

- **dataset** (`Dataset`) – Dataset containing records to be updated
- **updates** (`Iterable[Dict]`) – Each update should be formatted as specified in the [Public Docs for Dataset updates](#).

**Return type** `Dict[str, Any]`

**Returns** JSON response body from server

**Raises** `requests.HTTPError` – If an HTTP error is encountered

`record.stream(session, dataset)`

Stream the records in this dataset as Python dictionaries.

**Parameters** `dataset` (`Union[Dataset, UnifiedDataset]`) – Dataset from which to stream records

**Return type** `Iterator[Dict[str, Any]]`

**Returns** Python generator yielding records

## Dataframe

`dataframe.upsert(session, dataset, df, *, primary_key_name=None)`

Upserts a record for each row of `df` with attributes for each column in `df`.

**Parameters**

- **dataset** (`Dataset`) – Dataset to receive record updates
- **df** (`pd.DataFrame`) – The DataFrame containing records to be upserted
- **primary\_key\_name** (`Optional[str]`) – The primary key of the dataset. Must be a column of `df`. By default the `key_attribute_name` of dataset

**Return type** `Dict[str, Any]`

**Returns** JSON response body from the server

**Raises**

- `requests.HTTPError` – If an HTTP error is encountered
- `requests.HTTPError` – If an HTTP error is encountered
- `primary_key.NotFound` – If `primary_key_name` is not a column in `df` or the index of `df`
- `ValueError` – If `primary_key_name` matches both a column in `df` and the index of `df`

## Unified

`class tamr_client.dataset.unified.UnifiedDataset(url, name, key_attribute_names, description=None)`

A Tamr unified dataset

See <https://docs.tamr.com/reference/dataset-models>

**Parameters**

- **url** (URL) – The project-based alias for this dataset e.g. `/projects/1/unifiedDataset`
- **name** (`str`) –

- **key\_attribute\_names** (`Tuple[str, ...]`) –
- **description** (`Optional[str]`) –

`tamr_client.dataset.unified.from_project(session, instance, project)`  
Get unified dataset of a project

Fetches the unified dataset of a given project from Tamr server

#### Parameters

- **instance** (`Instance`) – Tamr instance containing this dataset
- **project** (`MasteringProject`) – Tamr project of this Unified Dataset

#### Raises

- **unified.NotFound** – If no unified dataset could be found at the specified URL. Corresponds to a 404 HTTP error.
- **requests.HTTPError** – If any other HTTP error is encountered.

#### Return type

`UnifiedDataset`

`tamr_client.dataset.unified.apply_changes(session, unified_dataset)`  
Applies changes to the unified dataset and waits for the operation to complete

**Parameters** `unified_dataset` (`UnifiedDataset`) – The Unified Dataset which will be committed

#### Return type

`Operation`

## Exceptions

`class tamr_client.dataset.unified.NotFound`

Raised when referencing (e.g. updating or deleting) a unified dataset that does not exist on the server.

## Instance

`class tamr_client.Instance(protocol='http', host='localhost', port=None)`

Connection parameters for a running Tamr instance

#### Parameters

- **protocol** (`str`) –
- **host** (`str`) –
- **port** (`Optional[int]`) –

`tamr_client.instance.origin(instance)`  
HTTP origin i.e. `<protocol>://<host>[:<port>]`.

For additional information, see [MDN web docs](#).

#### Return type

`str`

## Mastering

### Mastering Project

```
class tamr_client.MasteringProject(url, name, description=None)
A Tamr Mastering project
```

See <https://docs.tamr.com/reference/the-project-object>

#### Parameters

- **url** (URL) –
- **name** (str) –
- **description** (Optional[str]) –

## Operation

```
class tamr_client.Operation(url, type, status=None, description=None)
A Tamr operation
```

See <https://docs.tamr.com/new/reference/the-operation-object>

#### Parameters

- **url** (URL) –
- **type** (str) –
- **status** (Optional[Dict[str, str]]) –
- **description** (Optional[str]) –

```
tamr_client.operation.poll(session, operation)
```

Poll this operation for server-side updates.

Does not update the Operation object. Instead, returns a new Operation.

**Parameters** **operation** (Operation) – Operation to be polled.

**Return type** Operation

```
tamr_client.operation.wait(session, operation, *, poll_interval_seconds=3, timeout_seconds=None)
```

Continuously polls for this operation's server-side state.

#### Parameters

- **operation** (Operation) – Operation to be polled.
- **poll\_interval\_seconds** (int) – Time interval (in seconds) between subsequent polls.
- **timeout\_seconds** (Optional[int]) – Time (in seconds) to wait for operation to resolve.

**Raises** **TimeoutError** – If operation takes longer than *timeout\_seconds* to resolve.

**Return type** Operation

```
tamr_client.operation.succeeded(operation)
```

Convenience method for checking if operation was successful.

**Return type** bool

## Primary Key

### Exceptions

**class** tamr\_client.primary\_key.**Ambiguous**

Raised when referencing a primary key by name that matches multiple possible targets.

**class** tamr\_client.primary\_key.**NotFound**

Raised when referencing a primary key by name that does not exist.

## Project

tamr\_client.project.**from\_resource\_id**(session, instance, id)

Get project by resource ID

Fetches project from Tamr server

### Parameters

- **instance** (Instance) – Tamr instance containing this dataset
- **id(str)** – Project ID

### Raises

- **project.NotFound** – If no project could be found at the specified URL. Corresponds to a 404 HTTP error.
- **requests.HTTPError** – If any other HTTP error is encountered.

**Return type** MasteringProject

### Exceptions

**class** tamr\_client.project.**NotFound**

Raised when referencing (e.g. updating or deleting) a project that does not exist on the server.

## Response

Utilities for working with `requests.Response`.

tamr\_client.response.**successful**(response)

Ensure response does not contain an HTTP error.

Delegates to `requests.Response.raise_for_status()`

**Return type** Response

**Returns** The response being checked.

**Raises** `requests.exceptions.HTTPError` – If an HTTP error is encountered.

tamr\_client.response.**ndjson**(response, \*\*kwargs)

Stream newline-delimited JSON from the response body

Analog to `requests.Response.json()` but for .ndjson-formatted body.

**Recommended:** For memory efficiency, use `stream=True` when sending the request corresponding to this response.

### Parameters

- **response** (Response) – Response whose body should be streamed as newline-delimited JSON.
- **\*\*kwargs** – Keyword arguments passed to underlying `requests.Response.iter_lines()` call.

**Returns** Each line of the response body, parsed as JSON

### Example

```
>>> import tamr_client as tc
>>> s = tc.session.from_auth(...)
>>> r = s.get(..., stream=True)
>>> for data in tc.response.ndjson(r):
...     assert data['my_key'] == 'my_value'
```

**Return type** `Iterator[Dict[str, Any]]`

## Session

The Session type is an alias for `requests.Session`.

For more information, see the official [requests.Session](#) docs.

`tamr_client.session.from_auth(auth)`

Create a new authenticated session

**Parameters** `auth` (`HTTPBasicAuth`) – Authentication

**Return type** `Session`



## PYTHON MODULE INDEX

t

tamr\_client.record, 86



# INDEX

## A

add\_input\_dataset()  
    (*tamr\_unify\_client.categorization.project.CategorizationProject*  
        method), 29

add\_input\_dataset()  
    (*tamr\_unify\_client.mastering.project.MasteringProject*  
        method), 51

add\_input\_dataset()  
    (*tamr\_unify\_client.project.resource.Project*  
        method), 67

AlreadyExists (*class in tamr\_client.attribute*), 83

Ambiguous (*class in tamr\_client.primary\_key*), 90

apply\_changes() (*in module*  
    *tamr\_client.dataset.unified*), 88

apply\_options() (*tamr\_unify\_client.operation.Operation*  
    method), 56

as\_categorization()  
    (*tamr\_unify\_client.categorization.project.CategorizationProject*  
        method), 29

as\_categorization()  
    (*tamr\_unify\_client.mastering.project.MasteringProject*  
        method), 52

as\_categorization()  
    (*tamr\_unify\_client.project.resource.Project*  
        method), 66

as\_mastering() (*tamr\_unify\_client.categorization.project.CategorizationProject*  
    method), 29

as\_mastering() (*tamr\_unify\_client.mastering.project.MasteringProject*  
    method), 52

as\_mastering() (*tamr\_unify\_client.project.resource.Project*  
    method), 67

Attribute (*class in tamr\_client*), 81

Attribute (*class*  
    *tamr\_unify\_client.attribute.resource*), 23

attribute\_configurations()  
    (*tamr\_unify\_client.categorization.project.CategorizationProject*  
        method), 29

attribute\_configurations()  
    (*tamr\_unify\_client.mastering.project.MasteringProject*  
        method), 52

attribute\_configurations()  
    (*tamr\_unify\_client.project.resource.Project*  
        method), 67

*method*), 67

    attribute\_mappings()  
        (*tamr\_unify\_client.categorization.project.CategorizationProject*  
            method), 29

    attribute\_mappings()  
        (*tamr\_unify\_client.mastering.project.MasteringProject*  
            method), 52

    attribute\_mappings()  
        (*tamr\_unify\_client.project.resource.Project*  
            method), 67

    attribute\_name() (*tamr\_unify\_client.project.attribute\_configuration.*  
        *property*), 59

    attribute\_profiles()  
        (*tamr\_unify\_client.dataset.profile.DatasetProfile*  
            *property*), 44

    attribute\_role() (*tamr\_unify\_client.project.attribute\_configuration.*  
        *property*), 58

    AttributeCollection (*class*  
        *in*  
        *tamr\_unify\_client.attribute.collection*), 25

    AttributeConfiguration (*class*  
        *in*  
        *tamr\_unify\_client.project.attribute\_configuration.resource*),  
        58

    AttributeConfigurationCollection (*class in*  
        *tamr\_unify\_client.project.attribute\_configuration.collection*),  
        61

    AttributeConfigurationSpec (*class*  
        *in*  
        *tamr\_unify\_client.project.attribute\_configuration.resource*),  
        50

    AttributeMapping (*class*  
        *in*  
        *tamr\_unify\_client.project.attribute\_mapping.resource*),  
        62

    AttributeMappingCollection (*class*  
        *in*  
        *tamr\_unify\_client.project.attribute\_mapping.collection*),  
        65

    AttributeMappingSpec (*class*  
        *in*  
        *tamr\_unify\_client.project.attribute\_mapping.resource*),  
        64

    attributes() (*tamr\_unify\_client.attribute.type.AttributeType*  
        *property*), 26

    attributes() (*tamr\_unify\_client.categorization.project.CategorizationProject*  
        *property*), 29

    attributes() (*tamr\_unify\_client.dataset.resource.Dataset*

property), 36  
attributes () (tamr\_unify\_client.mastering.project.MasteringProject method), 33  
    property), 52  
attributes () (tamr\_unify\_client.project.resource.Project  
    property), 66  
AttributeSpec (class  
    tamr\_unify\_client.attribute.resource), 24  
AttributeType (class  
    tamr\_unify\_client.attribute.type), 26  
AttributeTypeSpec (class  
    tamr\_unify\_client.attribute.type), 27

by\_resource\_id () (tamr\_unify\_client.categorization.category.collection  
    method), 33  
    by\_resource\_id () (tamr\_unify\_client.dataset.collection.DatasetCollection  
        method), 41  
        by\_resource\_id () (tamr\_unify\_client.project.attribute\_configuration.  
            method), 61  
            by\_resource\_id () (tamr\_unify\_client.project.attribute\_mapping.collec  
                method), 65  
            by\_resource\_id () (tamr\_unify\_client.project.collection.ProjectCollect  
                method), 69

**C**

categories () (tamr\_unify\_client.categorization.taxonomy.Taxonomy  
    method), 34  
CategorizationProject (class  
    in Category (class in tamr\_unify\_client.categorization.category.resource),  
        31  
CategoryCollection (class  
    in tamr\_unify\_client.categorization.category.collection),  
        CategorySpec (class  
            in CategoryCollection  
                method), 32  
            CategoryCollection  
                (tamr\_unify\_client.mastering.estimated\_pair\_counts.EstimatedPair  
                    method), 33  
                Client (class in tamr\_unify\_client), 35  
by\_external\_id () (tamr\_unify\_client.attribute.collection.AttributeCollection  
    method), 25  
by\_external\_id () (tamr\_unify\_client.categorization.category.collection.Category  
    method), 33  
by\_external\_id () (tamr\_unify\_client.dataset.collection.DatasetCollection  
    method), 41  
by\_external\_id () (tamr\_unify\_client.project.attribute.configuration.collection.Attribute  
    method), 61  
by\_external\_id () (tamr\_unify\_client.project.collection.ProjectCollection  
    method), 69  
by\_name () (tamr\_unify\_client.attribute.collection.AttributeCollection  
    method), 26  
by\_name () (tamr\_unify\_client.dataset.collection.DatasetCollection  
    method), 33  
by\_name () (tamr\_unify\_client.project.collection.ProjectCollection  
    method), 42  
by\_relative\_id () (tamr\_unify\_client.attribute.collection.AttributeCollection  
    method), 25  
by\_relative\_id () (tamr\_unify\_client.categorization.category.collection.Category  
    method), 33  
by\_relative\_id () (tamr\_unify\_client.dataset.collection.DatasetCollection  
    method), 41  
by\_relative\_id () (tamr\_unify\_client.project.attribute\_configuration.collection.Attribute  
    method), 42  
by\_relative\_id () (tamr\_unify\_client.project.attribute\_mapping.collection.Attribute  
    method), 65  
by\_relative\_id () (tamr\_unify\_client.project.collection.ProjectCollection  
    method), 69  
by\_resource\_id () (tamr\_unify\_client.attribute.collection.AttributeCollection  
    method), 25

    CreationError (class  
        in tamr\_unify\_client.dataset.collection), 43

**D**

dataframe.upsert() (in module tamr\_client), 87  
**Dataset** (class in tamr\_client), 85  
**Dataset** (class in tamr\_unify\_client.dataset.resource), 36  
dataset() (tamr\_unify\_client.dataset.uri.DatasetURI method), 45  
dataset() (tamr\_unify\_client.dataset.use.DatasetUse method), 47  
dataset\_id() (tamr\_unify\_client.dataset.use.DatasetUse property), 46  
dataset\_name() (tamr\_unify\_client.dataset.profile.DatasetProfile property), 43  
dataset\_name() (tamr\_unify\_client.dataset.status.DatasetStatus property), 44  
dataset\_name() (tamr\_unify\_client.dataset.use.DatasetUse property), 46  
**DatasetCollection** (class in tamr\_unify\_client.dataset.collection), 41  
**DatasetProfile** (class in tamr\_unify\_client.dataset.profile), 43  
datasets() (tamr\_unify\_client.Client property), 36  
**DatasetSpec** (class in tamr\_unify\_client.dataset.resource), 40  
**DatasetStatus** (class in tamr\_unify\_client.dataset.status), 44  
**DatasetURI** (class in tamr\_unify\_client.dataset.uri), 45  
**DatasetUsage** (class in tamr\_unify\_client.dataset.usage), 46  
**DatasetUse** (class in tamr\_unify\_client.dataset.use), 46  
**DEFAULT** (in module tamr\_client.attribute.type), 83  
**delete()** (in module tamr\_client.attribute), 83  
**delete()** (tamr\_unify\_client.attribute.resource.Attribute method), 23  
**delete()** (tamr\_unify\_client.base\_model.MachineLearningModel method), 47  
**delete()** (tamr\_unify\_client.categorization.category.resource Category method), 31  
**delete()** (tamr\_unify\_client.categorization.project.CategorizationProject method), 30  
**delete()** (tamr\_unify\_client.categorization.taxonomy.Taxonomy property), 46  
**delete()** (tamr\_unify\_client.categorization.taxon.Taxon method), 34  
**delete()** (tamr\_unify\_client.Client method), 36  
**delete()** (tamr\_unify\_client.dataset.profile.DatasetProfile method), 44  
**delete()** (tamr\_unify\_client.dataset.resource.Dataset method), 39  
**delete()** (tamr\_unify\_client.dataset.status.DatasetStatus method), 45  
**delete()** (tamr\_unify\_client.dataset.usage.DatasetUsage method), 46  
**delete()** (tamr\_unify\_client.mastering.binning\_model.BinningModel method), 48  
**delete()** (tamr\_unify\_client.mastering.estimated\_pair\_counts.EstimatedPairCounts method), 49  
**delete()** (tamr\_unify\_client.mastering.project.MasteringProject method), 52  
**delete()** (tamr\_unify\_client.mastering.published\_cluster.configuration.PublishedClusterConfiguration method), 54  
**delete()** (tamr\_unify\_client.operation.Operation method), 58  
**delete()** (tamr\_unify\_client.project.attribute\_configuration.resource.AttributeConfiguration method), 59  
**delete\_file()** (tamr\_unify\_client.project.attribute\_mapping.resource.AttributeMapping method), 63  
**delete()** (tamr\_unify\_client.project.resource.Project method), 67  
**delete\_all\_records()** (tamr\_unify\_client.dataset.resource.Dataset method), 37  
**delete\_by\_resource\_id()** (tamr\_unify\_client.attribute.collection.AttributeCollection method), 26  
**delete\_by\_resource\_id()** (tamr\_unify\_client.categorization.category.collection.CategoryCollection method), 34  
**delete\_by\_resource\_id()** (tamr\_unify\_client.dataset.collection.DatasetCollection method), 42  
**delete\_by\_resource\_id()** (tamr\_unify\_client.project.attribute\_configuration.collection.AttributeConfiguration method), 62  
**delete\_by\_resource\_id()** (tamr\_unify\_client.project.attribute\_mapping.collection.AttributeMapping method), 66  
**delete\_by\_resource\_id()** (tamr\_unify\_client.project.collection.ProjectCollection method), 70  
**delete\_records()** (tamr\_unify\_client.dataset.resource.Dataset method), 37  
**delete\_records\_by\_id()** (tamr\_unify\_client.dataset.resource.Dataset method), 37  
**dependencies()** (tamr\_unify\_client.dataset.usage.DatasetUsage description) (tamr\_unify\_client.attribute.resource.Attribute property), 23  
**description()** (tamr\_unify\_client.categorization.category.resource.Category description) (tamr\_unify\_client.categorization.project.CategorizationProject property), 31  
**description()** (tamr\_unify\_client.categorization.taxon.Taxon description) (tamr\_unify\_client.attribute.resource.Attribute property), 30  
**description()** (tamr\_unify\_client.dataset.resource.Dataset description) (tamr\_unify\_client.dataset.resource.Dataset property), 36  
**description()** (tamr\_unify\_client.mastering.project.MasteringProject description) (tamr\_unify\_client.operation.Operation property), 52  
**description()** (tamr\_unify\_client.operation.Operation description) (tamr\_unify\_client.operation.Operation property), 58

```

    property), 57
from_response () (tamr_unify_client.operation.Operation
description () (tamr_unify_client.project.resource.Project      class method), 56
    property), 66
DOUBLE (in module tamr_client.attribute.type), 83

E
enabled_for_ml () (tamr_unify_client.project.attribute_configuration.resource.AttributeConfiguration
    property), 59
entity_id () (tamr_unify_client.mastering.published_cluster_record.PublishedCluster
    property), 55
estimate_pairs () (tamr_unify_client.mastering.project.MasteringProject
    method), 50
EstimatedPairCounts      (class      in  I
    tamr_unify_client.mastering.estimated_pair_counts)  I & (tamr_unify_client.mastering.published_cluster.resource.PublishedC
    48
external_id () (tamr_unify_client.categorization.project.CategorizationProject
    property), 30
external_id () (tamr_unify_client.dataset.resource.Dataset
    property), 36
external_id () (tamr_unify_client.mastering.project.MasteringProject
    property), 52
external_id () (tamr_unify_client.project.resource.Project
    property), 66

F
from_auth () (in module tamr_client.session), 91
from_data () (tamr_unify_client.attribute.resource.AttributeSpec
    method), 24
from_data () (tamr_unify_client.categorization.category.resource.CategorySpec
    method), 32
from_data () (tamr_unify_client.dataset.resource.DatasetSpec
    method), 40
from_data () (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
    method), 60
from_data () (tamr_unify_client.project.resource.ProjectSpec
    method), 68
from_dataset_all ()      (in      module  input_to_project_steps()
    tamr_client.attribute), 81
from_geo_features ()      (in      module  input_to_project_steps()
    tamr_unify_client.dataset.resource.Dataset
    method), 38
from_json () (in module tamr_client.attribute.sub), 84
from_json () (in module tamr_client.attribute.type),
    84
from_json () (tamr_unify_client.attribute.subattribute.SubAttribute
    static method), 28
from_project ()      (in      module  is_up_to_date ()
    tamr_client.dataset.unified), 88
from_resource_id ()      (in      module  is_up_to_date ()
    tamr_client.attribute), 81
from_resource_id ()      (in      module  iterategeofeatures ()
    tamr_client.dataset), 85
from_resource_id ()      (in      module  (tamr_unify_client.dataset.resource.Dataset
    tamr_client.project), 90
                                                method), 39

G
GEOSPATIAL (in module tamr_client.attribute.type), 84
get () (tamr_unify_client.Client method), 35

H
HIGH_IMPACT_PAIRS (in module tamr_unify_client.mastering.published_cluster_record.PublishedCluster
    property), 54
tamr_unify_client.project.attribute_mapping.resource.AttributeMapping
    property), 58
tamr_unify_client.project.attribute_mapping.resource.AttributeMapping
    property), 62
inner_type () (tamr_unify_client.attribute.type.AttributeType
    property), 26
input_attribute_id ()      (tamr_unify_client.project.attribute_mapping.resource.AttributeM
    property), 62
input_attribute_name ()      (tamr_unify_client.project.attribute_mapping.resource.AttributeM
    property), 63
input_dataset_name ()      (tamr_unify_client.project.attribute_mapping.resource.AttributeM
    property), 63
Input_datasets () (tamr_unify_client.categorization.project.Categoriz
    method), 30
Input_datasets () (tamr_unify_client.categorization.project.Categoriz
    method), 52
Input_datasets () (tamr_unify_client.project.resource.Project
    method), 67
Input_datasets () (tamr_unify_client.dataset.use.DatasetUse
    property), 46
Instance (class in tamr_client), 88
INT (in module tamr_client.attribute.type), 83
is_nullable () (tamr_unify_client.attribute.resource.Attribute
    property), 23
is_streamable () (tamr_unify_client.dataset.status.DatasetStatus
    property), 44
is_up_to_date () (tamr_unify_client.dataset.profile.DatasetProfile
    property), 43
is_up_to_date () (tamr_unify_client.mastering.estimated_pair_counts
    property), 48
iterategeofeatures ()      (tamr_unify_client.dataset.resource.Dataset
    method), 39

```

**K**

key\_attribute\_names()  
 (tamr\_unify\_client.dataset.resource.Dataset  
 property), 36

**L**

LONG (in module tamr\_client.attribute.type), 83

**M**

MachineLearningModel (class  
 tamr\_unify\_client.base\_model), 47

MasteringProject (class in tamr\_client), 89

MasteringProject (class  
 tamr\_unify\_client.mastering.project), 50

Metric (class in tamr\_unify\_client.mastering.published\_cluster.metric),  
 53

metrics() (tamr\_unify\_client.mastering.published\_cluster.version.  
 PublishedClusterVersion  
 property), 55

model() (tamr\_unify\_client.categorization.project.CategorizationProject  
 method), 28

module  
 tamr\_client.record, 86

**N**

name() (tamr\_unify\_client.attribute.resource.Attribute  
 property), 23

name() (tamr\_unify\_client.categorization.category.resource.Category  
 property), 31

name() (tamr\_unify\_client.categorization.project.CategorizationProject  
 property), 30

name() (tamr\_unify\_client.categorization.taxonomy.Taxonomy  
 property), 34

name() (tamr\_unify\_client.dataset.resource.Dataset  
 property), 36

name() (tamr\_unify\_client.mastering.project.MasteringProject  
 property), 52

name() (tamr\_unify\_client.mastering.published\_cluster.metric.Metric  
 property), 53

name() (tamr\_unify\_client.mastering.published\_cluster.version.PublishedClusterVersion  
 property), 55

name() (tamr\_unify\_client.project.resource.Project  
 property), 66

ndjson() (in module tamr\_client.response), 90

new() (tamr\_unify\_client.attribute.resource.AttributeSpec  
 static method), 24

new() (tamr\_unify\_client.attribute.type.AttributeTypeSpec  
 static method), 27

new() (tamr\_unify\_client.categorization.category.resource.CategorySpec  
 static method), 32

new() (tamr\_unify\_client.dataset.resource.DatasetSpec  
 static method), 40

new() (tamr\_unify\_client.project.attribute\_configuration.resource.AttributeConfigurationSpec  
 static method), 60

new() (tamr\_unify\_client.project.attribute\_mapping.resource.AttributeMap  
 static method), 64

new() (tamr\_unify\_client.project.resource.ProjectSpec  
 static method), 68

NotFound (class in tamr\_client.attribute), 83

NotFound (class in tamr\_client.dataset), 86

NotFound (class in tamr\_client.dataset.unified), 88

NotFound (class in tamr\_client.primary\_key), 90

NotFound (class in tamr\_client.project), 90

numeric\_field\_resolution()  
 in (tamr\_unify\_client.project.attribute\_configuration.resource.Attribute  
 property), 59

**O**

of() (tamr\_unify\_client.attribute.resource.AttributeSpec  
 static method), 24

of() (tamr\_unify\_client.attribute.type.AttributeTypeSpec  
 static method), 27

of() (tamr\_unify\_client.categorization.category.resource.CategorySpec  
 static method), 32

of() (tamr\_unify\_client.dataset.resource.DatasetSpec  
 static method), 40

of() (tamr\_unify\_client.project.attribute\_configuration.resource.Attribute  
 static method), 59

of() (tamr\_unify\_client.project.attribute\_mapping.resource.AttributeMap  
 static method), 64

of() (tamr\_unify\_client.project.resource.ProjectSpec  
 static method), 68

Operation (class in tamr\_client), 89

Operation (class in tamr\_unify\_client.operation), 56

origin() (in module tamr\_client.instance), 88

origin() (tamr\_unify\_client.Client property), 35

origin\_entity\_id()  
 (tamr\_unify\_client.mastering.published\_cluster.record.RecordPub  
 property), 55

origin\_source\_id()  
 (tamr\_unify\_client.mastering.published\_cluster.record.RecordPub  
 property), 55

output\_from\_project\_steps()  
 (tamr\_unify\_client.dataset.use.DatasetUse  
 property), 46

**P**

pair\_matching\_model()  
 (tamr\_unify\_client.mastering.project.MasteringProject  
 method), 50

pairs() (tamr\_unify\_client.mastering.project.MasteringProject  
 method), 50

parent() (tamr\_unify\_client.categorization.category.resource.Category  
 method), 31

path() (tamr\_unify\_client.categorization.category.resource.Category  
 method), 31

poll() (in module tamr\_client.operation), 89

```
poll()          (tamr_unify_client.operation.Operation
               method), 57
post()          (tamr_unify_client.Client method), 35
predict()        (tamr_unify_client.base_model.MachineLearningModel 55
               method), 47
profile()        (tamr_unify_client.dataset.resource.Dataset
               method), 38
profiled_at()    (tamr_unify_client.dataset.profile.DatasetProfile
               property), 43
profiled_data_version()  (tamr_unify_client.dataset.profile.DatasetProfile
               property), 43
Project          (class in tamr_unify_client.project.resource), 66
project()        (tamr_unify_client.project.step.ProjectStep
               method), 71
project_name()   (tamr_unify_client.project.step.ProjectStep
               property), 71
project_step_id()  (tamr_unify_client.project.step.ProjectStep
               property), 71
project_step_name()  (tamr_unify_client.project.step.ProjectStep
               property), 71
ProjectCollection  (class in tamr_unify_client.project.collection), 69
projects()       (tamr_unify_client.Client property), 36
ProjectSpec      (class in tamr_unify_client.project.resource), 68
ProjectStep      (class in tamr_unify_client.project.step), 71
published_cluster_ids()  (tamr_unify_client.mastering.project.MasteringProject
               method), 50
published_cluster_stats()  (tamr_unify_client.mastering.project.MasteringProject
               method), 51
published_cluster_versions()  (tamr_unify_client.mastering.project.MasteringProject
               method), 51
published_clusters()    (tamr_unify_client.mastering.project.MasteringProject
               method), 50
published_clusters_configuration()  (tamr_unify_client.mastering.project.MasteringProject
               method), 50
published_clusters_with_data()  (tamr_unify_client.mastering.project.MasteringProject
               method), 51
PublishedCluster    (class in tamr_unify_client.mastering.published_cluster.resource), 54
PublishedClustersConfiguration  (class in tamr_unify_client.mastering.published_cluster.configuration), 43
PublishedClusterVersion  (class in tamr_unify_client.mastering.published_cluster.version), 54
put()             (tamr_unify_client.attribute.resource.AttributeSpec
               method), 25
put()             (tamr_unify_client.Client method), 36
putProfile()      (tamr_unify_client.dataset.resource.DatasetSpec
               method), 41
put()             (tamr_unify_client.project.attribute_configuration.resource.AttributeSpec
               method), 61
put()             (tamr_unify_client.project.resource.ProjectSpec
               method), 69
```

## R

```
Record          (class in tamr_client.attribute.type), 84
Record._update()  (in module tamr_client), 86
record.delete()   (in module tamr_client), 86
record.stream()   (in module tamr_client), 87
record.upsert()   (in module tamr_client), 86
record_clusters()  (tamr_unify_client.mastering.project.MasteringProject
               method), 50
record_clusters_with_data()  (tamr_unify_client.mastering.project.MasteringProject
               method), 51
record_ids()      (tamr_unify_client.mastering.published_cluster.version.property), 55
record_published_cluster_versions()  (tamr_unify_client.mastering.project.MasteringProject
               method), 51
RecordPublishedCluster  (class in tamr_unify_client.mastering.published_cluster.record), 55
RecordPublishedClusterVersion  (class in tamr_unify_client.mastering.published_cluster.record_version), 56
records()         (tamr_unify_client.dataset.resource.Dataset
               method), 38
records()         (tamr_unify_client.mastering.binning_model.BinningModel
               method), 47
refresh()         (tamr_unify_client.dataset.profile.DatasetProfile
               method), 44
refresh()         (tamr_unify_client.dataset.resource.Dataset
               method), 37
refresh()         (tamr_unify_client.mastering.estimated_pair_counts.Estimate
               method), 49
refresh_attribute_id()  (tamr_unify_client.project.attribute_configuration.resource.AttributeSpec
               method), 58
refresh_dataset_id()  (tamr_unify_client.dataset.profile.DatasetProfile
               method), 43
refresh_dataset_id()  (tamr_unify_client.dataset.resource.Dataset
               method)
```

```

(tamr_unify_client.dataset.status.DatasetStatus    ReservedName (class in tamr_client.attribute), 83
property), 44                                     resource_id() (tamr_unify_client.attribute.resource.Attribute
relative_id() (tamr_unify_client.attribute.resource.Attribute    property), 24
property), 23                                     resource_id() (tamr_unify_client.base_model.MachineLearningMode
relative_id() (tamr_unify_client.base_model.MachineLearningModel    property), 47
property), 47                                     resource_id() (tamr_unify_client.categorization.category.resource.Cat
relative_id() (tamr_unify_client.categorization.category.resource.Category    egory), 31
property), 31                                     resource_id() (tamr_unify_client.categorization.project.Categorizati
relative_id() (tamr_unify_client.categorization.project.Categorizati    onProject), 30
property), 30                                     resource_id() (tamr_unify_client.categorization.taxonomy.Taxonomy
relative_id() (tamr_unify_client.categorization.taxonomy.Taxonomy    property), 34
property), 34                                     resource_id() (tamr_unify_client.dataset.profile.DatasetProfile
relative_id() (tamr_unify_client.dataset.profile.DatasetProfile    property), 44
property), 44                                     resource_id() (tamr_unify_client.dataset.resource.Dataset
relative_id() (tamr_unify_client.dataset.resource.Dataset    property), 39
property), 39                                     resource_id() (tamr_unify_client.dataset.status.DatasetStatus
relative_id() (tamr_unify_client.dataset.status.DatasetStatus    property), 45
property), 45                                     resource_id() (tamr_unify_client.dataset.uri.DatasetURI
relative_id() (tamr_unify_client.dataset.uri.DatasetURI    property), 45
property), 45                                     resource_id() (tamr_unify_client.dataset.usage.DatasetUsage
relative_id() (tamr_unify_client.dataset.usage.DatasetUsage    property), 46
property), 46                                     resource_id() (tamr_unify_client.mastering.binning_model.BinningM
relative_id() (tamr_unify_client.mastering.binning_model.BinningModel    odel), 48
property), 48                                     resource_id() (tamr_unify_client.mastering.estimated_pair_counts.E
relative_id() (tamr_unify_client.mastering.estimated_pair_counts.E    stimatedPairCounts
property), 49                                     resource_id() (tamr_unify_client.mastering.project.MasteringProject
relative_id() (tamr_unify_client.mastering.project.MasteringProject    property), 53
property), 53                                     resource_id() (tamr_unify_client.mastering.published_cluster.configu
relative_id() (tamr_unify_client.mastering.published_cluster.configuration    ration), 54
property), 54                                     resource_id() (tamr_unify_client.operation.Operation
relative_id() (tamr_unify_client.operation.Operation    property), 58
property), 58                                     resource_id() (tamr_unify_client.project.attribute_configuration.reso
relative_id() (tamr_unify_client.project.attribute_configuration.reso    urce), 59
property), 59                                     resource_id() (tamr_unify_client.project.attribute_mapping.resource.
relative_id() (tamr_unify_client.project.attribute_mapping.resource    ), 62
property), 62                                     resource_id() (tamr_unify_client.project.resource.Project
relative_id() (tamr_unify_client.project.resource.Project    property), 68
property), 68                                     S
relative_input_attribute_id()                               AttributeMapping
(tamr_unify_client.project.attribute_mapping.resource.AttributeMapping    ation()
property), 62                                     (tamr_unify_client.project.attribute_configuration.resource.Attrib
relative_unified_attribute_id()                           ute
(property), 63                                     (tamr_unify_client.project.attribute_mapping.resource.AttributeMapping
remove_input_dataset()                                (tamr_unify_client.dataset.profile.DatasetProfile
(property), 30                                     property), 43
source_id() (tamr_unify_client.mastering.published_cluster.record.Rec
method), 30                                     property), 55
spec() (tamr_unify_client.attribute.resource.Attribute
remove_input_dataset()                                type)
(property), 53                                     (tamr_unify_client.attribute.type.AttributeType
method), 23                                     method), 27
spec() (tamr_unify_client.categorization.category.resource.Category
remove_input_dataset()                                (tamr_unify_client.categorization.project.Categorizati
(property), 67                                     onProject), 30
request() (tamr_unify_client.Client method), 35

```

```
spec() (tamr_unify_client.dataset.resource.Dataset timestamp() (tamr_unify_client.mastering.published_cluster.version.Pu  
method), 39  
property), 55  
spec() (tamr_unify_client.mastering.project.MasteringProject dict() (tamr_unify_client.attribute.resource.AttributeSpec  
method), 53  
method), 24  
spec() (tamr_unify_client.mastering.published_cluster.configAttribute(PublishedDatasetConfigurationType.AttributeTypeSpec  
method), 54  
method), 27  
spec() (tamr_unify_client.project.attribute_configuration.resource.AttributeConfiguration.categorization.category.resource.Category  
method), 59  
method), 32  
spec() (tamr_unify_client.project.attribute_mapping.resource.AttributeMapping tamr_unify_client.dataset.resource.DatasetSpec  
method), 63  
method), 40  
spec() (tamr_unify_client.project.resource.Project to_dict() (tamr_unify_client.project.attribute_configuration.resource.A  
method), 67  
method), 60  
state() (tamr_unify_client.operation.Operation prop- to_dict() (tamr_unify_client.project.attribute_mapping.resource.Attribu  
erty), 57  
method), 64  
status() (tamr_unify_client.dataset.resource.Dataset to_dict() (tamr_unify_client.project.resource.ProjectSpec  
method), 38  
method), 68  
stream() (tamr_unify_client.attribute.collection.AttributeCollection () (in module tamr_client.attribute), 82  
method), 26  
to_json() (in module tamr_client.attribute.sub), 84  
stream() (tamr_unify_client.categorization.category.collection.CategorizationCategoryCollection (in module tamr_client.attribute.type), 84  
method), 33  
tokenizer() (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationCollection  
method), 41  
total_estimate() (tamr_unify_client.mastering.estimated_pair_coun  
method), 61  
train() (tamr_unify_client.base_model.MachineLearningModel  
method), 65  
AttributeMappingCollection  
type() (tamr_unify_client.attribute.resource.Attribute  
method), 47  
type() (tamr_unify_client.project.collection.ProjectCollection property), 23  
method), 70  
type() (tamr_unify_client.categorization.project.CategorizationProject  
property), 30  
STRING (in module tamr_client.attribute.type), 83  
SubAttribute (class in tamr_unify_client.attribute.subattribute),  
in type() (tamr_unify_client.mastering.project.MasteringProject  
28  
property), 53  
type() (tamr_unify_client.operation.Operation prop-  
erty), 57  
erty), 58  
type() (tamr_unify_client.project.resource.Project  
method), 66  
type() (tamr_unify_client.project.step.ProjectStep  
successful() (in module tamr_client.response), 90  
property), 71
```

## T

```
tags() (tamr_unify_client.dataset.resource.Dataset  
property), 36  
tamr_client.attribute.type.Array (built-in  
class), 84  
tamr_client.attribute.type.Map (built-in  
class), 84  
tamr_client.record  
module, 86  
tamr_client.SubAttribute (built-in class), 84  
Taxonomy (class in tamr_unify_client.categorization.taxonomy),  
34  
taxonomy() (tamr_unify_client.categorization.project.CategorizationProject  
method), 29  
timestamp() (tamr_unify_client.mastering.published_cluster.configAttribute.RecordPublishedClusterVersion  
property), 56  
method), 66
```

## U

```
unified_attribute_id() (tamr_unify_client.project.attribute_mapping.resource.AttributeMapping  
property), 63  
unified_attribute_name() (tamr_unify_client.project.attribute_mapping.resource.AttributeMapping  
property), 63  
unified_dataset() (tamr_unify_client.categorization.project.CategorizationProject  
method), 30  
unified_dataset()  
unified_dataset()  
method), 53  
method), 53  
RecordPublishedClusterVersion  
method), 66
```

```

unified_dataset_name()                                with_attributes()
    (tamr_unify_client.project.attribute_mapping.resource.AttributeMapping.client.attribute.type.AttributeTypeSpec
     property), 63                                     method), 27
UnifiedDataset          (class                      in   with_base_type() (tamr_unify_client.attribute.type.AttributeTypeSpec
     tamr_client.dataset.unified), 87                  method), 27
update() (in module tamr_client.attribute), 82      with_description()
update_records() (tamr_unify_client.mastering.binning_model.BinningModel.client.attribute.resource.AttributeSpec
     method), 48                                         method), 24
upsert_from_dataframe()                            with_description()
    (tamr_unify_client.dataset.resource.Dataset
     method), 37                                         method), 32
upsert_records() (tamr_unify_client.dataset.resource.Dataset
     method), 37                                         DatasetDescription()
upstream_datasets()                               with_description()
    (tamr_unify_client.dataset.resource.Dataset
     method), 39                                         ProjectSpec
uri() (tamr_unify_client.dataset.uri.DatasetURI prop-   method), 68
     erty), 45                                         with_enabled_for_ml()
usage() (tamr_unify_client.dataset.resource.Dataset   with_external_id()
     method), 38                                         (tamr_unify_client.dataset.resource.DatasetSpec
     property), 46                                         method), 40
usage() (tamr_unify_client.dataset.usage.DatasetUsage with_external_id()
     property), 46                                         (tamr_unify_client.project.resource.ProjectSpec
     method), 69                                         method), 69
UsernamePasswordAuth (class in tamr_client), 85
UsernamePasswordAuth (class           in   with_inner_type()
     tamr_unify_client.auth), 28
V
value() (tamr_unify_client.mastering.published_cluster.metric.Metric.client.attribute.type.AttributeTypeSpec
     property), 53                                     method), 27
version() (tamr_unify_client.dataset.resource.Dataset with_input_attribute_id()
     property), 36                                         (tamr_unify_client.project.attribute_mapping.resource.AttributeM
     method), 64
version() (tamr_unify_client.mastering.published_cluster.record.method).RecordPublishedClusterVersion
     property), 56                                         with_input_attribute_name()
version() (tamr_unify_client.mastering.published_cluster.version.publishedClusterVersion
     property), 55                                         publishedClusterVersion
     method), 64
versions() (tamr_unify_client.mastering.published_cluster.publishedCluster)
     property), 55                                         with_is_nullable()
     method), 64                                         (tamr_unify_client.attribute.resource.AttributeSpec
     property), 54                                         method), 40
versions_time_to_live()                           with_key_attribute_names()
    (tamr_unify_client.mastering.published_cluster.configuration.publishedClustersConfiguration
     property), 54                                         (tamr_unify_client.dataset.resource.DatasetSpec
     method), 65                                         method), 40
W
wait() (in module tamr_client.operation), 89
wait()          (tamr_unify_client.operation.Operation
     method), 57                                         with_name()
with_attribute_name()                            with_name()
    (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
     method), 60                                         method), 24
with_attribute_role()                           with_name()
    (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
     method), 60                                         with_name()
                                         method), 68
                                         with_numeric_field_resolution()
                                         (tamr_unify_client.project.attribute_configuration.resource.Attribute

```

```
        method), 60
with_path () (tamr_unify_client.categorization.category.resource.CategorySpec
        method), 32
with_relative_input_attribute_id ()
        (tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec
        method), 64
with_relative_unified_attribute_id ()
        (tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec
        method), 65
with_similarity_function ()
        (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
        method), 60
with_tags () (tamr_unify_client.dataset.resource.DatasetSpec
        method), 41
with_tokenizer () (tamr_unify_client.project.attribute_configuration.resource.AttributeConfigurationSpec
        method), 60
with_traceback () (tamr_unify_client.dataset.collection.CreationError
        method), 43
with_type () (tamr_unify_client.attribute.resource.AttributeSpec
        method), 24
with_type () (tamr_unify_client.project.resource.ProjectSpec
        method), 68
with_unified_attribute_id ()
        (tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec
        method), 64
with_unified_attribute_name ()
        (tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec
        method), 65
with_unified_dataset_name ()
        (tamr_unify_client.project.attribute_mapping.resource.AttributeMappingSpec
        method), 65
with_unified_dataset_name ()
        (tamr_unify_client.project.resource.ProjectSpec
        method), 69
```